

WEST 1/16TH CORNER SOUTHWEST QUARTER OF SECTION 27, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) STEVEN S. BROSEMER, L.S. 752, IN SURVEYS F27001 AND F27002 IN THE SURVEY FILE FOR TOWNSHIP 20-11 TO LOCATE THE NORTHWEST AND SOUTHWEST CORNERS OF THE SOUTH HALF OF THE SOUTH HALF OF THE NORTHWEST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 27-20-11 FOR PROJECT NUMBER 98638-02 DATED JANUARY 19, 1999 SHOWS ON HIS SURVEY DRAWING THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 27-20-11 ON LINE AND HALF WAY BETWEEN THE WEST 1/4 CORNER AND THE SOUTHWEST CORNER OF SECTION 27-20-11.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 330.44' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE S1/2 OF THE S1/2 OF THE NW1/4 OF THE SW1/4 OF SECTION 27-20-11
 - 2) 1,321.77' NORTH TO THE KDOT ALUMINUM CAP HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 27-20-11
 - 3) 1,321.77' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 27-20-11
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED JUNE 14, 2002, FOR PROJECT NUMBER 02228-02, SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE SURVEY OF TRACTS OF LAND IN THE NORTH HALF OF THE SOUTHEAST QUARTER OF SECTION 28-20-11, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS "LS 752" CAP** AT THE EAST 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-20-11 FROM HIS PREVIOUS SURVEY.
- 1) 35.2' ENE TO A CONCRETE NAIL & SHINER IN A POWER POLE
 - 2) 24.9' EAST TO A CONCRETE NAIL & SHINER IN A CORNER FENCE POST
 - 3) IN LINE WITH A FENCE TO THE EAST
 - 4) 10.5' EAST TO THE CENTERLINE TRAVELED WAY OF THE COUNTY ROAD NORTH-SOUTH
 - 5) 3.5' SOUTH TO A LINE OF FENCE TO THE WEST [EXTENDED]
 - 6) 24.2' WSW TO THE NEAR FACE AT THE BASE OF A PIPE POST
- HIS DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 1,321.78' NORTH TO THE KDOT ALUMINUM CAP HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 28-20-11 FROM HIS PREVIOUS SURVEY
 - 2) 1,325.25' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE S1/2 OF THE NW1/4 OF THE SE1/4 OF SEC. 28-20-11
 - 3) 2,650.50' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF THE N1/2 OF THE SE1/4 OF SEC. 28-20-11

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 27-20-11