

**NORTH 1/16<sup>TH</sup> CORNER NORTHWEST QUARTER OF SECTION 29, TOWNSHIP 20 SOUTH,  
RANGE 11 EAST**

- 1) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR 4 TRACTS IN THE WEST HALF OF THE WEST HALF OF SECTION 29-20-11 DATED SEPTEMBER 17 & 18, 1974 SHOWS ON HIS SURVEY DRAWING A “**TEMPORARY POINT**” AT THE NORTH 1/16<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 29-20-11 TO BE ON LINE AND HALFWAY BETWEEN THE NORTHWEST CORNER AND THE NORTH 1/4 CORNER OF SECTION 29-20-11.

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,327’ WEST TO THE “PIN” AT THE NORTHWEST CORNER OF SECTION 29-20-11
  - 2) 1,327’ EAST TO THE TEMPORARY POINT AT THE NORTH 1/4 CORNER OF SECTION 29-20-11
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 06, 2000, FOR JOB NUMBER 99316-02, SURVEY F29004 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE EAST HALF OF THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 29-20-11, SAID THAT **HE SET A 1/2” X 24” REBAR WITH A CAP** FOR THE NORTH 1/16<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 29-20-11 ON TRUE LINE AND HALF WAY BETWEEN THE NORTHWEST CORNER AND THE NORTH 1/4 CORNER OF SECTION 29-20-11.
- 1) 61.45’ ENE TO A 40 D NAIL IN A RAILROAD TIE BRACE POST
  - 2) 15.85’ SSE TO A CONCRETE NAIL IN A CORNER FENCE POST
  - 3) 7.5’ NORTH TO THE CENTERLINE TRAVELED WAY OF THE COUNTY ROAD EAST-WEST
  - 4) 5.3’ EAST TO THE CENTERLINE OF A FENCE TO THE SOUTH EXTENDED

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 660.38’ WEST TO THE 1/2” REBAR WITH HIS “LS 752” CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF THE NW1/4 OF SECTION 29-20-11
- 2) 1,320.76’ WEST TO THE 5/8” REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-20-11 FROM HIS 1983 PERMANENT SURVEY
- 3) 1,320.76’ EAST TO THE 5/8” REBAR HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 29-20-11 FROM HIS 1983 PERMANENT SURVEY
- 4) 1,320.3’ SOUTH TO THE 1/2” REBAR WITH HIS “LS 752” CAP HE SET FOR THE SOUTHEAST CORNER OF THE E1/2 OF THE NW1/4 OF THE NW1/4 OF SEC. 29-19-11
- 5) 2,640.6’ SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 29-20-11

NORTH SIXTEENTH CORNER NORTHWEST QUARTER 29-20-11