

**WEST 1/16TH CORNER NORTHWEST QUARTER OF SECTION 29, TOWNSHIP 20 SOUTH,
RANGE 11 EAST**

- 1) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 DATED SEPTEMBER 17 & 18, 1974 SHOWS A PIN AT THE WEST 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 29-20-11. THIS CORNER IS ALSO THE NORTHWEST CORNER OF TRACT I
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,326' NORTH TO THE "PIN" AT THE NORTHWEST CORNER OF SECTION 29-20-11
 - 2) 663' SOUTH TO THE "PIN" AT THE SOUTHWEST CORNER OF TRACT I
 - 3) 1,326' SOUTH TO THE "PIN" AT THE WEST 1/4 CORNER OF SECTION 29-20-11 AND THE NORTHWEST CORNER OF TRACT III
 - 4) 1,986' SOUTH TO THE "PIN" AT THE SOUTHWEST CORNER OF TRACT III
 - 5) 2,646' SOUTH TO THE "PIN" AT THE WEST 1/16TH CORNER OF THE SW1/4 OF SECTION 29-20-11 AND THE SOUTHWEST CORNER OF TRACT IV
 - 6) 3,966' SOUTH TO THE "PIN" AT THE SOUTHWEST CORNER OF SECTION 29-20-11
 - 7) 1,326' EAST TO THE "PIN" AT THE CENTER CORNER OF THE NE1/4 OF SECTION 29-20-11 AND THE NORTHEAST CORNER OF TRACT I

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 06, 2000, FOR JOB NUMBER 99316-02, SURVEY F29004 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE EAST HALF OF THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 29-20-11, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE WEST 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 29-20-11 ON TRUE LINE AND HALF WAY BETWEEN THE NORTHWEST CORNER AND THE WEST 1/4 CORNER OF SECTION 29-20-11.
 - 1) 21.2' ESE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 2) 21.85' EAST TO A 40 D SPIKE IN A POWER POLE
 - 3) 12.15' NORTH TO A CROP LINE TO THE EAST EXTENDED
 - 4) 3.7' WEST TO THE CENTERLINE TRAVELED WAY OF THE COUNTY ROAD NORTH-SOUTHHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,320.22' NORTH TO THE 5/8" REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-20-11 FROM HIS 1983 PERMANENT SURVEY
 - 2) 1,320.22' SOUTH TO THE LOCATION FOR THE WEST 1/4 CORNER OF SECTION 29 – MONUMENT NOW GONE AS IT FALLS ON A CULVERT, ATTRIBUTABLE TO L. M. GOULD'S BAR FROM A PERMANENT SURVEY
 - 3) 3,959.85' SOUTH TO THE 1/2" REBAR FOUND AT THE SOUTHWEST CORNER OF SECTION 29-20-11
 - 4) 660.73' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF THE NW1/4 OF SECTION 29-20-11
 - 5) 1,321.46' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE E1/2 OF THE NW1/4 OF THE NW1/4 OF SEC. 29-20-11
 - 6) 2,642.91' EAST TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 29-20-11

WEST SIXTEENTH CORNER NORTHWEST QUARTER 29-20-11