

**WEST 1/16TH CORNER SOUTHEAST QUARTER OF SECTION 29, TOWNSHIP 20 SOUTH,
RANGE 11 EAST**

1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED FEBRUARY 18, 2003, FOR PROJECT NUMBER 01220-02, SURVEY F29005 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE NORTHEAST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 29-20-11, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE EAST 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-20-11 ON TRUE LINE AND HALFWAY BETWEEN THE SOUTH 1/4 CORNER AND THE CENTER CORNER OF SECTION 29-20-11. IN HIS *REPORT OF SURVEY* HE COMMENTED: "I WAS AWARE [IN HIS 1983 OFFICIAL SURVEY RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 61] THEN AND NOW OF A SURVEY SIGNED BY L. M. GOULD, L.S. 142, DATED SEPT. 1974 THAT SUPPOSEDLY SURVEYED THE SW1/4 NW1/4 AND THE NW1/4 SW1/4 INTO FOUR ALIQUOT PART TRACTS. I FOUND THIS 1974 SURVEY TO HAVE BEEN **IMPROPERLY DONE**, AS THE WEST HALF OF THE WEST HALF OF SECTION 29 WAS **NOT** SUBDIVIDED ACCORDING TO STATUTORY REQUIREMENTS. BECAUSE OF THIS, I DID NOT HONOR THE MONUMENTS THAT WERE SET ON THE GOULD SURVEY DURING THE COURSE OF THE 1983 OFFICIAL SURVEY OR ON ANY SUBSEQUENT SURVEYS BY ME."

- 1) 3.0' EAST TO A CORNER FENCE POST
- 2) 3.0' EAST TO A FENCE LINE TO THE NORTH
- 3) IN LINE WITH A FENCE TO THE WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323.74' NORTH TO THE 5/8" REBAR HE FOUND AT THE CENTER CORNER OF SECTION 29-20-11 FROM HIS 1983 PERMANENT SURVEY
- 2) 1,323.74' SOUTH TO THE 5/8" REBAR HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 29-20-11 FROM HIS 1983 PERMANENT SURVEY
- 3) 1,322.55' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTH-WEST CORNER OF THE NE1/4 OF THE SW1/4 OF SECTION 29-20-11
- 4) 2,645.10' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 OF THE SW1/4 OF SECTION 29-20-11

WEST SIXTEENTH CORNER SOUTHEAST QUARTER 29-20-11