

**WEST 1/16TH CORNER SOUTHWEST QUARTER OF SECTION 29, TOWNSHIP 20 SOUTH,
RANGE 11 EAST**

- 1) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR 4 TRACTS IN THE WEST HALF OF THE WEST HALF OF SECTION 29-20-11 DATED SEPTEMBER 17 & 18, 1974 SHOWS ON HIS SURVEY DRAWING A “PIN” AT THE WEST 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-20-11 ON LINE AND HALFWAY BETWEEN THE WEST 1/4 CORNER AND THE SOUTHWEST CORNER OF SECTION 29-20-11. THIS IS ALSO THE SOUTHWEST CORNER OF TRACT IV.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,320’ SOUTH TO THE “PIN” AT THE SOUTHWEST CORNER OF SECTION 29-20-11
 - 2) 660’ NORTH TO THE “PIN” AT THE NORTHWEST CORNER OF TRACT IV
 - 3) 1,320’ NORTH TO THE “PIN” AT THE WEST 1/4 CORNER OF SECTION 29-20-11 AND THE NORTHWEST CORNER OF TRACT III
 - 4) 1,983’ NORTH TO THE “PIN” AT THE NORTHWEST CORNER OF TRACT II
 - 5) 2,646’ NORTH TO THE “PIN” AT THE WEST 1/16TH CORNER OF THE NW1/4 OF SECTION 29-20-11 AND THE NORTHWEST CORNER OF TRACT I
 - 6) 3,972’ NORTH TO THE PIN AT THE NORTHWEST CORNER OF SECTION 29-20-11
 - 7) 1,324’ EAST TO THE “PIN” AT THE CENTER CORNER OF THE SW1/4 OF SECTION 29-20-11 AND THE SOUTHEAST CORNER OF TRACT IV
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F29005 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE NORTHEAST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 29-20-11 FOR PROJECT NUMBER 01220-02 DATED NOVEMBER 4, 2002 SHOWS ON HIS SURVEY DRAWING THAT **HE SET A 1/2” REBAR WITH HIS “LS 752” CAP** FOR THE WEST 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-20-11 ON LINE AND HALF WAY BETWEEN THE SOUTHWEST CORNER AND THE LOCATION FOR THE WEST 1/4 CORNER OF SECTION 29-20-11. IN HIS *REPORT OF SURVEY* HE COMMENTED: “I WAS AWARE [IN HIS 1983 OFFICIAL SURVEY RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 61] THEN AND NOW OF A SURVEY SIGNED BY L. M. GOULD, L.S. 142, DATED SEPT. 1974 THAT SUPPOSEDLY SURVEYED THE SW1/4 NW1/4 AND THE NW1/4 SW1/4 INTO FOUR ALIQUOT PART TRACTS. I FOUND THIS 1974 SURVEY TO HAVE BEEN **IMPROPERLY DONE**, AS THE WEST HALF OF THE WEST HALF OF SECTION 29 WAS **NOT** SUBDIVIDED ACCORDING TO STATUTORY REQUIREMENTS. BECAUSE OF THIS, I DID NOT HONOR THE MONUMENTS THAT WERE SET ON THE GOULD SURVEY DURING THE COURSE OF THE 1983 OFFICIAL SURVEY OR ON ANY SUBSEQUENT SURVEYS BY ME.”
- 1) FELL 1.5’ SOUTH OF THE EAST-WEST FENCE AND 5.0’ WEST OF A FENCE TO THE NORTH
 - 2) A REBAR [GOULD] WAS FOUND ABOUT 2’ SOUTH AND ABOUT 4.5’ EAST OF THE MONUMENTED POSITION
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 1,319.82’ SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-20-11
 - 2) 1,319.82’ NORTH TO THE LOCATION FOR THE WEST 1/4 CORNER OF SECTION 29-20-11 –MONUMENT NOW GONE, FALLS ON A CULVERT, POSITION DETERMINED FROM HIS PERMANENT SURVEY
 - 3) 1,322.55’ EAST TO THE 1/2" REBAR WITH HIS “LS 752” CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF THE SW1/4 OF SECTION 29-20-11
 - 4) 2,654.10’ EAST TO THE 1/2" REBAR HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF THE SW1/4 OF SECTION 29-20-11

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 29-20-11