

WEST 1/4 CORNER SECTION 31, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 39 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 10" X 4-1/2"** FOR THE WEST 1/4 CORNER OF SECTION 31-20-11 ON THE WEST TOWNSHIP BOUNDARY ON NOVEMBER 25, 1856.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 24" X 12" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-20-11
 - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 35" X 10" X 2-1/2" LIMESTONE THEY SET ON A SLOPE TO THE EAST FOR THE CORNER TO TOWNSHIP 20 SOUTH, RANGES 10 & 11 EAST ON THE 4TH STANDARD PARALLEL AT THE SOUTHWEST CORNER OF SECTION 31-20-11

- 2) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 8, 1984, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE EAST 1/4 CORNER OF SECTION 36-20-10 ON THE RANGE LINE, BUT HE DID **NOT** FIND THE STONE. HE DETERMINED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE EAST 1/4 CORNER OF SECTION 36-20-10 BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER; I.E., IN LINE WITH THE FENCES EAST & WEST AND IN THE CENTER OF THE ROAD RIGHT-OF-WAY.
 - 1) 26.0' EAST AND WEST TO A LINE OF FENCES TO THE NORTH
 - 2) IN LINE WITH FENCES TO THE EAST AND WEST [EXTENDED]
 - 3) IN THE TRAVELED WAY OF THE ROAD NORTH-SOUTH

WEST QUARTER CORNER 31-20-11