

NORTH 1/4 CORNER SECTION 32, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 400 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 15" X 12" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 32-20-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.03 CHAINS WEST TO THE 16" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-20-11
 - 2) 40.03 CHAINS EAST TO THE 20" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-20-11

- 2) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR 4 TRACTS IN THE WEST HALF OF THE WEST HALF OF SECTION 29-20-11 DATED SEPTEMBER 17 & 18, 1974 SHOWS ON HIS SURVEY DRAWING A "**TEMPORARY POINT**" FOR THE SOUTH 1/4 CORNER OF SECTION 29-20-11.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,323' WEST TO THE TEMPORARY POINT FOR THE SOUTH 1/16TH CORNER OF THE SW1/4 OF SECTION 29-20-11
 - 2) 2,646' WEST TO THE "PIN" AT THE SOUTHWEST CORNER OF SECTION 29-20-11

- 3) STEVEN S. BROSEMER, L.S. 752, APPOINTED COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 61 TO PERMANENTLY ESTABLISH THE EAST LINE OF THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 29-20-11 PETITIONED BY BEVERLY CROOK THAT BEGAN ON SEPTEMBER 21, 1983 AND CONTINUED UNTIL COMPLETION ON SEPTEMBER 26, 1983, SAID THAT HE EXCAVATED BY HAND FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 29-20-11, BUT **NO** STONE WAS FOUND IN THE ROAD CUT. **HE SET A #5 REBAR WITH A LYON COUNTY CAP** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 29-20-11 ON THIS **PERMANENT SURVEY**. IN AN ORANGE K & E FILED BOOK LABELED "JULY 1983" IN THE VAULT IN THE COUNTY ENGINEERS OFFICE UNDER "S 1/4 CORNER" OF 29-20-11E", IT STATES THAT HE RESET THIS CORNER BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER: I.E. IN LINE WITH A HEDGEROW TO THE SOUTH AND A LINE OF FENCE TO THE NORTH AND IN THE CENTER OF THE RIGHT-OF-WAY FENCES. THIS SURVEY IS FILED IN VOLUME 403 ON PAGE 641 IN THE REGISTER OF DEEDS OFFICE AND SURVEY F29006 IN THE SURVEY FILE FOR TOWNSHIP 20-11. THE FOLLOWING TIES ARE ON THE PERMANENT SURVEY:
 - 1) 20.0' NORTH TO A LINE OF FENCE TO THE WEST
 - 2) 20.0' SOUTH TO A LINE OF FENCE TO THE WEST
 - 3) IN THE TRAVELED WAY OF THE ROAD EAST-WESTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,646.07' WEST TO THE #4 REBAR HE FOUND AND HE ACCEPTED FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 29-20-11
 - 2) 5,282.27' WEST TO A LINE OF FENCE TO THE SOUTH AND A LINE OF HEDGE TO THE NORTH
 - 3) 2,647.83' NORTH TO THE #5 REBAR WITH A YELLOW LYON COUNTY CAP HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 29-20-11
 - 4) 5,288.33' NORTH TO THE #5 REBAR WITH A YELLOW LYON COUNTY CAP HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 29-20-11
 - 5) 2,642.0' EAST TO A LINE OF FENCE TO THE NORTH AND A SPLIT OF THE RIGHT-OF-WAY FENCES TO THE SOUTH
 - 6) 5,286.0' EAST TO A SPLIT OF THE RIGHT-OF-WAY FENCES TO THE SOUTH

CONTINUED ON PAGE 2

- 4) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 8, 1999, FOR JOB NUMBER 99532-02, SURVEY F33001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE SURVEY OF A 7.00 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 33-20-11 FOR KUHLMAN, SAID THAT **SHE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP AT THE NORTH 1/4 CORNER OF SECTION 32-20-11 FROM EXISTING TIES OF RECORD FROM THE 1983 PERMANENT SURVEY RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 61 IN THE COUNTY ENGINEER'S OFFICE.**
- 1) 78.45' WSW TO A 40 D SPIKE & BOTTLE CAP IN A POWER POLE
 - 2) 1.5' NORTH TO THE CENTERLINE COUNTY OF COUNTY ROAD 80 [EAST-WEST]
 - 3) 21.2' NORTH TO A MASONRY NAIL & BOTTLE CAP IN A CORNER FENCE POST
 - 4) 20.4' SOUTH TO A MASONRY NAIL & BOTTLE CAP IN A CORNER FENCE POST
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,643.01' EAST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTHWEST CORNER OF SECTION 33-20-11
 - 2) 5,290.87' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTH 1/4 CORNER OF SECTION 33-20-11
 - 3) 7,938.72' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE FOUND AT THE NORTHEAST CORNER OF SECTION 33-20-11
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 18, 2003, FOR PROJECT NUMBER 01220-02, SURVEY F29005 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE NORTHEAST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 29-20-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP AT THE SOUTH 1/4 CORNER OF SECTION 29-20-11 FROM HIS EXISTING TIES OF RECORD FROM HIS 1983 PERMANENT SURVEY RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 61 IN THE COUNTY ENGINEER'S OFFICE. IN HIS REPORT OF SURVEY HE COMMENTED: "I WAS AWARE THEN AND NOW OF A SURVEY SIGNED BY L. M. GOULD, L.S. 142, DATED SEPT. 1974 THAT SUPPOSEDLY SURVEYED THE SW1/4 NW1/4 AND THE NW1/4 SW1/4 INTO FOUR ALIQUOT PART TRACTS. I FOUND THIS 1974 SURVEY TO HAVE BEEN IMPROPERLY DONE, AS THE WEST HALF OF THE WEST HALF OF SECTION 29 WAS NOT SUBDIVIDED ACCORDING TO STATUTORY REQUIREMENTS. BECAUSE OF THIS, I DID NOT HONOR THE MONUMENTS THAT WERE SET ON THE GOULD SURVEY DURING THE COURSE OF THE 1983 OFFICIAL SURVEY OR ON ANY SUBSEQUENT SURVEYS BY ME."**
- 1) IN LINE WITH A FENCE TO THE NORTH
 - 2) IN LINE WITH A HEDGE TO THE SOUTH
 - 3) IN THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST [GRAVEL]
 - 4) 21.2' NORTH TO A MASONRY NAIL & BOTTLE CAP IN A CORNER FENCE POST
 - 5) 20.4' SOUTH TO A MASONRY NAIL & BOTTLE CAP IN A CORNER FENCE POST
 - 6) 78.5' WSW TO A 40 D SPIKE & BOTTLE CAP IN A POWER POLE
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,322.96' WEST TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE SW1/4 OF SECTION 29-20-11
 - 2) 2,645.93' WEST TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-20-11
 - 3) 1,323.74' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF THE SW1/4 OF SECTION 29-20-11
 - 4) 2,647.48' NORTH TO THE 5/8" REBAR HE FOUND AT THE CENTER CORNER OF SECTION 29-20-11 FROM HIS 1983 PERMANENT SURVEY
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 31, 2004, FOR PROJECT NUMBER 04088-02, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE SUBDIVISION OF THE SOUTHWEST QUARTER OF SECTION 32-20-11, SAID THAT **HE FOUND THE**

5/8" REBAR WITH A LYON COUNTY CAP AT THE NORTH 1/4 CORNER OF SECTION 32-20-11 FROM HIS EXISTING TIES OF RECORD FROM HIS 1983 PERMANENT SURVEY RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 61 IN THE COUNTY ENGINEER'S OFFICE.

- 1) IN LINE WITH A FENCE TO THE NORTH
- 2) IN LINE WITH A HEDGE TO THE SOUTH
- 3) IN THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST [GRAVEL]
- 4) 21.2' NORTH TO A MASONRY NAIL & BOTTLE CAP IN A CORNER FENCE POST
- 5) 20.4' SOUTH TO A MASONRY NAIL & BOTTLE CAP IN A CORNER FENCE POST
- 6) 78.5' WSW TO A 40 D SPIKE & BOTTLE CAP IN A POWER POLE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,643.03' EAST TO THE 1/2" REBAR WITH A "LS 1130" CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 32-20-11
- 2) 2,630.14' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE N1/2 OF THE SW1/4 OF SECTION 32-20-11
- 3) 3,947.28' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE S1/2 OF THE SW1/4 OF SECTION 32-20-11
- 4) 5,264.42' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 32-20-11

NORTH QUARTER CORNER 32-20-11