

NORTH 1/16TH CORNER NORTHWEST QUARTER OF SECTION 32, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) OAKES, DOLE & BISHOP, STATE HIGHWAY COMMISSION SURVEYORS, IN THE 1929 SURVEY FOR HIGHWAY K-11 [NOW K-99] FROM EMPORIA SOUTH TO THE GREENWOOD COUNTY LINE, SAID THAT **THEY SET A SPIKE FROM THE SPLIT OF THE FENCES** FOR THE SOUTH 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 27-20-11. SEE THEIR NOTES ON PAGE 12 OF THE FILED NOTES MARKED "KDOT 1" IN THE SURVEY FILE FOR TOWNSHIP 21-11.

- 1) 20' NORTH TO A FENCE LINE EAST-WEST
- 2) 20' SOUTH TO A FENCE LINE EAST-WEST

THEIR SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,322.9' EAST TO THE 5/8" IRON BAR THEY SET FOR THE SOUTH 1/4 CORNER OF SECTION 27-20-11
- 2) 3,968.6' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-20-11

- 2) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR 4 TRACTS IN THE WEST HALF OF THE WEST HALF OF SECTION 29-20-11 DATED SEPTEMBER 17 & 18, 1974 SHOWS ON HIS SURVEY DRAWING A "**TEMPORARY POINT**" AT THE SOUTH 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-20-11 TO BE ON LINE AND HALFWAY BETWEEN THE SOUTHWEST CORNER AND THE SOUTH 1/4 CORNER OF SECTION 29-20-11.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323' WEST TO THE "PIN" AT THE SOUTHWEST CORNER OF SECTION 29-20-11
- 2) 1,323' EAST TO THE TEMPORARY POINT FOR THE SOUTH 1/4 CORNER OF SECTION 29-20-11

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F29005 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE NORTHEAST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 29-20-11 FOR PROJECT NUMBER 01220-02 DATED NOVEMBER 14, 2002, SHOWS ON HIS SURVEY DRAWING THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE SOUTH 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-20-11 TO BE ON LINE AND HALF WAY BETWEEN THE SOUTHWEST AND SOUTH 1/4 CORNER OF SECTION 29-20-11, BUT THE POSITION WAS **NOT** MONUMENTED ON THIS SURVEY. IN HIS *REPORT OF SURVEY* HE COMMENTED: "I WAS AWARE [IN HIS 1983 OFFICIAL SURVEY RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 61] THEN AND NOW OF A SURVEY SIGNED BY L. M. GOULD, L.S. 142, DATED SEPT. 1974 THAT SUPPOSEDLY SURVEYED THE SW1/4 NW1/4 AND THE NW1/4 SW1/4 INTO FOUR ALIQUOT PART TRACTS. I FOUND THIS 1974 SURVEY TO HAVE BEEN **IMPROPERLY DONE**, AS THE WEST HALF OF THE WEST HALF OF SECTION 29 WAS **NOT** SUBDIVIDED ACCORDING TO STATUTORY REQUIREMENTS. BECAUSE OF THIS, I DID NOT HONOR THE MONUMENTS THAT WERE SET ON THE GOULD SURVEY DURING THE COURSE OF THE 1983 OFFICIAL SURVEY OR ON ANY SUBSEQUENT SURVEYS BY ME."

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,322.97' WEST TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-20-11
- 2) 1,322.96' EAST TO THE 5/8" REBAR FROM HIS 1983 PERMANENT SURVEY HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 29-20-11
- 3) 1,321.78' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF THE SW1/4 OF SECTION 29-20-11
- 4) 2,643.56' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF THE SW1/4 OF SECTION 29-20-11

NORTH SIXTEENTH CORNER NORTHWEST QUARTER 32-20-11