

SOUTH 1/4 CORNER SECTION 32, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 16 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE ROCK 19" X 10" X 3"** ON A SLOPE TO THE WEST FOR THE SOUTH 1/4 CORNER OF SECTION 32-20-11 ON THE 4TH STANDARD PARALLEL ON NOVEMBER 17, 1855.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE 4TH STANDARD PARALLEL TO THE 18" X 10" X 2-1/2" LIMESTONE THEY SET ON LEVEL GROUND FOR THE CORNER TO SECTIONS 31 & 32-20-11
 - 2) 40.00 CHAINS EAST ON THE 4TH STANDARD PARALLEL TO THE 20" X 8" X 3" LIMESTONE THEY SET ON A SLOPE TO THE EAST FOR THE CORNER TO SECTIONS 32 & 33-20-11
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 31, 2004, FOR PROJECT NUMBER 04088-02, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 20-11, SAID THAT HE DEEMED THAT THE SOUTH 1/4 CORNER OF SECTION 32-20-11 ON THE 4TH STANDARD PARALLEL WAS **LOST**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 32-20-11 ON THE 4TH STANDARD PARALLEL AT HALFWAY BETWEEN THE SOUTHWEST CORNER AND THE *SOUTH QUARTER CORNER OF SECTION 32-20-11* [**NOTE:** HIS SURVEY DRAWING SHOWS IT IS ON TRUE LINE AND HALFWAY BETWEEN THE SOUTHWEST CORNER AND THE SOUTHEAST CORNER OF SECTION 32-20-11 - WARREN CHIP WOODS, COUNTY SURVEYOR].
- 1) 66.15' NNW TO A 40 D NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
 - 2) 20.0' NORTH TO THE NORTH FACE OF THE HUBGUARD
 - 3) 58.8' SW TO THE SOUTHEAST CORNER OF THE SOUTH HUBGUARD
 - 4) 12.5' WEST TO A LINE OF FENCE TO THE NORTH [EXTENDED]
 - 5) 6.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 70 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,985.77' WEST ON THE 4TH STANDARD PARALLEL TO THE 40 D NAIL HE SET FOR THE SOUTHEAST CORNER OF THE WEST 20 ACRES OF THE S1/2 OF THE SW1/4 OF SECTION 32-20-11, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 50' NORTH
 - 2) 2,646.42' WEST ON THE 4TH STANDARD PARALLEL TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE S1/2 OF THE SW1/4 OF SECTION 32-20-11
 - 3) 2,646.42' EAST ON THE 4TH STANDARD PARALLEL TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 32-20-11
 - 4) 1,317.14' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE S1/2 OF THE SW1/4 OF SECTION 32-20-11
 - 5) 2,634.28' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE N1/2 OF THE SW1/4 OF SECTION 32-20-11
 - 6) 5,264.42' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 32-20-11
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 24, 2013 FOR PROJECT NUMBER 13124-02, THE SURVEY OF A 5.00 ACRE TRACT IN THE SOUTHEAST 1/4 OF SECTION 5-21-11 FOR TONY REDEKER, SURVEY F05002 IN THE SURVEY FILE FOR TOWNSHIP 21-11, SAID THAT **HE FOUND THE 5/8" IRON PIN WITH A LYON COUNTY CAP** AT THE SOUTH 1/4 CORNER OF SECTION 32-20-11 ON THE 4TH STANDARD PARALLEL FROM HIS

REFERENCE TIES ON FILE AT THE LYON COUNTY ENGINEERS OFFICE DATED MARCH 2004.

- 1) 66.15' NNW TO A 40 D NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
- 2) 20.0' NORTH TO THE NORTH FACE OF THE NORTH HUBGUARD
- 3) 58.8' SW TO THE SOUTHEAST CORNER OF THE SOUTH HUBGUARD
- 4) 12.5' WEST TO A LINE OF FENCE TO THE NORTH EXTENDED
- 5) 6.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 70 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,178.15' EAST ON THE 4TH STANDARD PARALLEL TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 5-21-11
- 2) 2,646.29' EAST ON THE 4TH STANDARD PARALLEL TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 32-10-11

SOUTH QUARTER CORNER 32-20-11