

**SOUTHWEST CORNER SECTION 32, TOWNSHIP 20 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 15 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE ROCK 18" X 10" X 2-1/2"** ON LEVEL GROUND FOR THE CORNER TO SECTIONS 31 & 32-20-11 ON THE 4<sup>TH</sup> STANDARD PARALLEL ON NOVEMBER 17, 1855.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 19" X 10" X 3" LIMESTONE THEY SET ON A SLOPE TO THE WEST FOR THE SOUTH 1/4 CORNER OF SECTION 32-20-11
  - 2) 80.00 CHAINS EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 20" X 8" X 3" LIMESTONE THEY SET ON A SLOPE TO THE EAST FOR THE CORNER TO SECTIONS 32 & 33-20-11
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 196 TO 198 [PACKET 61 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY L. O. PRIEST AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 20-11, 20-12 AND 21-11 THAT HE SURVEYED FEBRUARY 1-3, 1872, AND WAS ESTABLISHED AND ORDERED RECORDED BY THE BOARD OF COUNTY COMMISSIONERS AS A 50 FOOT WIDE ROAD ON APRIL 1, 1872 AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT **HE FOUND** THE SOUTHWEST CORNER OF SECTION 32-20-11 ON THE 4<sup>TH</sup> STANDARD PARALLEL ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE RIGHT BANK OF EAGLE CREEK IN THE SE1/4 OF SECTION 34-20-11 AT A TURN TO THE NORTHEASTERLY; THEN INTERSECTS THE 4<sup>TH</sup> STANDARD PARALLEL ON THE LEFT BANK OF EAGLE CREEK AT 1 MILE AND 7-1/2 RODS WEST OF THE CORNER TO SECTIONS 35 & 36-20-11; THEN CONTINUES EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL FOR 1 MILE AND 7-1/2 RODS TO THE CORNER OF SECTIONS 35 & 36-20-11 AT A TURN TO THE NORTH
- 2) THIS ROAD EXTENDS WEST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE WEST LINE OF RANGE 11, TOWNSHIP 20 AT THE SOUTHWEST CORNER OF SECTION 31-20-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 3) ROAD NUMBER 690 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 47:

DEEDED FROM JOHN SCHWINDT AND EMMA SCHWINDT TO LYON COUNTY RECORDED IN VOLUME 102 ON PAGE 539 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 6, 1915:

- 1) BEGINNING AT A STONE 1,332 FEET NORTH OF THE SOUTHEAST CORNER OF SECTION 31-20-11 ON THE SECTION LINE VAR 9°30'; THENCE N. 29°45' W. FOR 257 FEET TO A STONE; THENCE N. 27°10' E. FOR 117.75 FEET TO A STONE 20 FEET WEST OF THE SECTION LINE; THENCE NORTH PARALLEL TO AND 20 FEET WEST OF THE SECTION LINE TO A STONE
  - 2) THE ABOVE DESCRIBED LINE BEING THE CENTER LINE OF A 40 FOOT ROAD, 20 FEET ON EACH SIDE OF THE LINE, AND CONTAINING 64/100 OF AN ACRE
- 4) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 28, 1999, FOR PROJECT NUMBER 99532-02, SURVEY F33001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE SURVEY OF A 7.00 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 33-20-11 FOR KUHLMAN, SAID THAT SHE DETERMINED A **THEORETICAL POSITION** FOR THE SOUTHWEST CORNER OF SECTION 32-20-11 ON THE 4<sup>TH</sup> STANDARD PARALLEL. SHE DID **NOT** MONUMENT THE POSITION FOR THE SOUTHWEST CORNER OF SECTION 32-20-11 ON THIS SURVEY.

HER INFORMATION IS CONTINUED ON PAGE 2

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,292.78' WEST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-20-11 ON THE RANGE LINE
- 2) 5,292.78' EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTHWEST CORNER OF SECTION 33-20-11
- 3) 7,939.17' EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTH 1/4 CORNER OF SECTION 33-20-11
- 4) 10,585.56' EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTHEAST CORNER OF SECTION 33-20-11
- 5) 13,230.09' EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE FOUND AT THE SOUTH 1/4 CORNER OF SEC. 34-20-11

- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 11, 2000, FOR JOB NUMBER 00070-01, SAID THAT HE EXCAVATED FOR THE STONE AT THE SOUTHWEST CORNER OF SECTION 32-20-11 ON THE 4<sup>TH</sup> STANDARD PARALLEL. HE SAID THAT **PIECES OF STONE FOUND IN THE AREA WERE RESET** ON THE 4<sup>TH</sup> STANDARD PARALLEL BETWEEN THE SOUTHWEST CORNER OF SECTION 31-20-11 AND THE SOUTHEAST CORNER OF SECTION 32-20-11 AT A DIRECT PRORATION. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP AMONG THE STONE PIECES** FOR THE SOUTHWEST CORNER OF SECTION 32-20-11.

- 1) 67.0' NE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 2) 51.6' SSE TO A CONCRETE NAIL & WASHER IN A POWER POLE
- 3) 88.5' ENE TO THE SOUTHWEST CORNER OF A TELEPHONE PEDESTAL
- 4) 4.0' WEST TO THE CENTERLINE TRAVELED WAY OF THE COUNTY ROAD TO THE NORTH

HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:

- 1) 5,292.78' WEST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 5/8" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-20-11 ON THE RANGE LINE
- 2) 5,292.78' EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 32-20-11
- 3) 2,637.76' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 32-20-11
- 4) 5,275.52' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-20-11

- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 31, 2004, FOR PROJECT NUMBER 04088-02, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE SUBDIVISION OF THE SOUTHWEST QUARTER OF SECTION 32-20-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP AMONG THE STONE PIECES** AT THE SOUTHWEST CORNER OF SECTION 32-20-11 ON THE 4<sup>TH</sup> STANDARD PARALLEL FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED APRIL 11, 2000.

- 1) 67.0' NE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 2) 88.5' ENE TO THE SOUTHWEST CORNER OF A TELEPHONE PEDESTAL
- 3) 51.6' SSE TO A CONCRETE NAIL & WASHER IN A POWER POLE
- 4) 4.0' WEST TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "H" TO THE NORTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,318.93' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE S1/2 OF THE SW1/4 OF SECTION 32-20-11

HIS INFORMATION IS CONTINUED ON PAGE 3

- 2) 2,637.87' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE N1/2 OF THE SW1/4 OF SECTION 32-20-11
- 3) 660.65' EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 40 D NAIL HE SET FOR THE SOUTHEAST CORNER OF THE WEST 20 ACRES OF THE S1/2 OF THE SW1/4 OF SECTION 32-20-11, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET 50' NORTH
- 4) 2,646.42' EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 32-20-11
- 5) 5,292.84' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 32-20-11

SOUTHWEST CORNER 32-20-11