

**WEST 1/4 CORNER SECTION 32, TOWNSHIP 20 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 399 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 13" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 31 & 32-20-11.
  
- 2) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F31001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE SURVEY OF A 7 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 31-20-11, BUT NOT DATED, SHOWS ON HIS SURVEY DRAWING A **"TEMPORARY POINT"** AT THE EAST 1/4 CORNER OF SECTION 31-20-11.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 529.5' NORTH TO THE "PIN SET" FOR THE SOUTHEAST CORNER OF THE 7 ACRE TRACT
  - 2) 1,046.5' NORTH TO THE "PIN SET" FOR THE NORTHEAST CORNER OF THE 7 ACRE TRACT
  - 3) 1,320.5' NORTH TO THE "PIN" AT THE NORTHEAST CORNER OF THE SE1/4 OF THE NE1/4 OF SECTION 31-20-11
  - 4) 2,641' NORTH TO THE "PIN" AT THE NORTHEAST CORNER OF SECTION 31-20-11
  
- 3) STEVEN S. BROSEMER, L.S. 752, APPOINTED COUNTY SURVEYOR, IN A SURVEY RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 61 AT THE REQUEST OF BEVERLY CROOK TO ESTABLISH THE EAST LINE OF THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 29-20-11, DOES **NOT** MENTION THE WEST 1/4 CORNER OF SECTION 32-20-11 ON THIS **PERMANENT SURVEY**. HE NOTED ON HIS DRAWING THAT A LINE OF FENCE TO THE WEST WAS LOCATED 2,641.0' SOUTH OT THE #4 REBAR THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-20-11. THIS SURVEY IS FILED IN VOLUME 403 ON PAGE 641 IN THE REGISTER OF DEEDS OFFICE, AND SURVEY F29006 IN THE SURVEY FILE FOR TOWNSHIP 20-11. THE SURVEY BEGAN ON SEPTEMBER 21, 1983 AND WAS COMPLETED ON SEPTEMBER 26, 1983.
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 11, 2000, FOR JOB NUMBER 00070-01, SAID THAT HE EXCAVATED FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION 32-20-11, BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THIS CORNER WAS **LOST**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE WEST 1/4 CORNER OF SECTION 32-20-11 ON TRUE LINE AND HALF WAY BETWEEN THE OPPOSITE SECTION CORNERS.
  - 1) 29.4' SE TO A CONCRETE NAIL & WASHER IN A GATE POST
  - 2) 25.0' ESE TO A SPIKE & WASHER IN A CORNER FENCE POST
  - 3) 3.0' SOUTH TO A LINE OF FENCE TO THE EAST [EXTENDED]
  - 4) 102.5' NNE TO A CONCRETE NAIL & WASHER IN A POWER POLE
  - 5) 775.0' SOUTH TO A 1/2" X 24" REBAR WITH A "GEOTECH" CAP ON THE SECTION LINEHIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:
  - 1) 2,637.76' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-20-11
  - 2) 2,637.76' SOUTH TO THE 5/8" CAPPED REBAR HE SET OF THE SOUTHWEST CORNER OF SECTION 32-20-11 ON THE 4<sup>TH</sup> STANDARD PARALLEL
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 31, 2004, FOR PROJECT NUMBER 04088-02, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE SUBDIVISION OF THE SOUTHWEST QUARTER OF SECTION 32-20-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE WEST 1/4 CORNER OF SECTION

32-20-11 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED APRIL 2000.

- 1) 25.0' ESE TO A SPIKE & WASHER IN A CORNER FENCE POST
- 2) 29.4' SW TO A CONCRETE NAIL & WASHER IN A GATE POST
- 3) 102.5' NNE TO A CONCRETE NAIL & WASHER IN A POWER POLE
- 4) 3.0' SOUTH TO A LINE OF FENCE TO THE EAST [EXTENDED]
- 5) 775.0' SOUTH TO A 1/2" REBAR WITH A "GEOTECH" CAP FOUND [ON THE SECTION LINE]

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,314.94' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE S1/2 OF THE SW1/4 OF SECTION 32-20-11
- 2) 2,637.87' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE S1/2 OF THE SW1/4 OF SECTION 32-20-11 ON THE 4<sup>TH</sup> STANDARD PARALLEL
- 3) 2,645.98' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE N1/2 OF THE SW1/4 OF SECTION 32-20-11
- 4) 5,290.71' EAST TO THE THEORETICAL POSITION FOR THE EAST 1/4 CORNER OF SECTION 32-20-11 [FALLS IN A CREEK]

WEST 1/4 CORNER 32-20-11