

SOUTH 1/4 CORNER SECTION 34, TOWNSHIP 20 SOUTH, RANGE 11 EAST

- 1) ON PAGE 16 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE ROCK 17" X 11" X 3"** ON A SLOPE TO THE SOUTH FOR THE SOUTH 1/4 CORNER OF SECTION 34-20-11 ON THE 4TH STANDARD PARALLEL ON NOVEMBER 17, 1855.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST ON THE 4TH STANDARD PARALLEL TO THE 19" X 10" X 3" LIMESTONE THEY SET ON LEVEL GROUND FOR THE CORNER TO SECTIONS 33 & 34-20-11
 - 2) 40.00 CHAINS EAST ON THE 4TH STANDARD PARALLEL TO THE 25" X 9" X 2-1/2" LIMESTONE THEY SET ON LEVEL GROUND FOR THE CORNER TO SECTIONS 34 & 35-20-11

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 26 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 173 DATED MARCH 25, 1872 TO ESTABLISH THE CORNERS TO THE EAST AND WEST HALVES OF THE SOUTHWEST 1/4 OF SECTION 34-20-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 34-20-11 ON THE 4TH STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,327' WEST ON THE 4TH STANDARD PARALLEL TO THE POST HE SET ON THE HIGH PRAIRIE FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 34-20-11
 - 2) 2,654' WEST ON THE 4TH STANDARD PARALLEL TO THE STONE HE FOUND AT THE CORNER OF SECTIONS 33 & 34-20-11

- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 20-11 SHOWS A **STONE** AT THE "S1/4 CORNER SECTION 34-20-11" ON THE 4TH STANDARD PARALLEL.
 - 1) 43.1' NE TO AN IRON PIN
 - 2) 35.9' NW TO A CORNER FENCE POST
 - 3) 43' SW TO AN IRON PIN
 - 4) 37.1' SE TO A K. E. P. POLE

- 4) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 60 IN THE MIDDLE OF THE PAGE SHOWS A **STONE** AT THE "S1/4 CORNER SECTION 34-20-11" ON THE 4TH STANDARD PARALLEL.
 - 1) 35.9' NW TO A CEMETERY CORNER FENCE POST
 - 2) 43.0' SW TO AN IRON PIN
 - 3) 37.1' SE TO THE NEAR FACE OF A POWER POLE

- 5) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F34002 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE SURVEY OF A TRACT IN THE SOUTHWEST QUARTER OF SECTION 34-20-11 BUT NOT DATED, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTH 1/4 CORNER OF SECTION 34-20-11 ON THE 4TH STANDARD PARALLEL IN THE CENTER OF THE "WENDLING ROAD". THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 340' NORTH TO THE "MONUMENT" HE SET FOR THE SOUTHEAST TRACT CORNER – NOT DESCRIBED
 - 2) 900' NORTH TO THE "MONUMENT" HE SET FOR THE NORTHEAST TRACT CORNER – NOT DESCRIBED

CONTINUED ON PAGE 2

- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 15, 1994, FOR PROJECT NUMBER 94075-02, SURVEY F34003 IN THE SURVEY FILE FOR TOWNSHIP 20-11 LOCATE THE NORTHWEST CORNER OF SECTION 34-20-11 ORDERED BY THE BOARD OF COUNTY COMMISSIONERS AT THE REQUEST OF THE COUNTY SURVEYOR, SAID IN HIS *SURVEY NOTES* THAT THE SOUTH 1/4 CORNER OF SECTION 34-20-11 ON THE 4TH STANDARD PARALLEL HAD NO RECORD MONUMENT. TIES TO THE STONE WERE FOUND [1935] IN THE COUNTY TIE BOOKS, BEFORE THE ROAD WAS IMPROVED. HE EXCAVATED WITH A LYON COUNTY BACKHOE IN THE ASPHALT ROAD FOR THE STONE WITHOUT SUCCESS. THE CORNER WAS DEEMED **LOST**. **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 34-20-11 ON THE 4TH STANDARD PARALLEL AT HALFWAY BETWEEN THE SOUTHWEST CORNER OF SECTION 34-20-11 AND THE SOUTHEAST CORNER OF SECTION 34-20-11.
- 1) 44.5' NW TO THE TOP OF A TELEPHONE PEDESTAL
 - 2) 63.8' NE TO A CONCRETE NAIL & WASHER IN A POWER POLE
 - 3) 53.3' SE TO A CONCRETE NAIL & WASHER IN A POWER POLE
 - 4) 7.0' EAST TO THE TRAVELED WAY TO THE NORTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,644.52' WEST ON THE 4TH STANDARD PARALLEL TO THE KDOT REBAR WITH AN ALUMINUM CAP HE FOUND AT THE SOUTHWEST CORNER OF SEC. 34-20-11
 - 2) 2,644.52' EAST ON THE 4TH STANDARD PARALLEL TO THE KDOT REBAR WITH AN ALUMINUM CAP HE FOUND AT THE SOUTHEAST CORNER OF SEC. 34-20-11
 - 3) 2,623.99' NORTH TO THE 1/2" REBAR HE FOUND AT THE CENTER CORNER OF SECTION 34-20-11
 - 4) 5,280.34' NORTH TO THE KDOT REBAR WITH AN ALUMINUM CAP HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 34-20-11
- 7) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 28, 1999, FOR JOB NUMBER 99532-02, SURVEY F33001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE SURVEY OF A 7.00 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 33-20-11 FOR KUHLMAN, SAID THAT **SHE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE SOUTH 1/4 CORNER OF SECTION 34-20-11 ON THE 4TH STANDARD PARALLEL FROM TIES BY STEPHEN BROSEMER, LS 752, FOR JOB NUMBER 94075-02 DATED 04/15/1994.
- 1) 44.5' NW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 2) 63.8' NE TO A CONCRETE NAIL & WASHER IN A POWER POLE
 - 3) 53.3' SE TO A CONCRETE NAIL & WASHER IN A POWER POLE
 - 4) 7.0' EAST TO THE CENTERLINE OF COUNTY ROAD "K" RUNNING NORTH
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,644.53' WEST ON THE 4TH STANDARD PARALLEL TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTHEAST CORNER OF SECTION 33-20-11
 - 2) 5,290.92' WEST ON THE 4TH STANDARD PARALLEL TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTH 1/4 CORNER OF SECTION 33-20-11
 - 3) 7,937.31' WEST ON THE 4TH STANDARD PARALLEL TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTHWEST CORNER OF SECTION 33-20-11
 - 4) 13,230.09' WEST ON THE 4TH STANDARD PARALLEL TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF SECTION 32-20-11
 - 5) 18,522.87' WEST ON THE 4TH STANDARD PARALLEL TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE FOUND AT THE SOUTHWEST CORNER OF SEC. 31-20-11
- 8) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 10, 2001, FOR PROJECT NUMBER 01-59, SETTING COUNTY MONUMENT BOXES OVER SECTION CORNERS IN COUNTY ASPHALT ROADS, **FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP AT THE INTERSECTION OF COUNTY ROADS 70 & "K"** AT THE SOUTH 1/4 CORNER OF

- SECTION 34-20-11 ON THE 4TH STANDARD PARALLEL FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, DATED DECEMBER 28, 1999. **I REPLACED THIS FOUND 5/8" REBAR WITH A 5/8" X 24" REBAR WITH A LYON COUNTY CAP, AND I SET A LYON COUNTY MONUMENT BOX FLUSH WITH THE SURFACE OF THE ASPHALT ROAD INTERSECTION OF COUNTY ROAD 70 AND COUNTY ROAD "K" FOR THE SOUTH 1/4 CORNER OF SECTION 34-20-11 ON THE 4TH STANDARD PARALLEL.**
- 1) 45.7' NW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 2) 53.1' NW TO THE TOP CENTER OF A CORNER POST FOR A CHAIN-LINK FENCE AT THE CEMETERY: FENCES NORTH & SOUTHWEST
 - 3) 63.7' NE TO A FOUND CONCRETE NAIL & WASHER IN A POWER POLE
 - 4) 67.2' ENE TO THE TOP CENTER OF A FIBER OPTIC TELEPHONE CABLE MARKER POST
 - 5) 53.6' SE TO A FOUND CONCRETE NAIL & WASHER IN A POWER POLE
 - 6) IN THE TRAVELED WAY OF ASPHALT COUNTY ROAD 70 EAST-WEST
 - 7) 7' EAST TO THE TRAVELED WAY OF ASPHALT COUNTY ROAD "K5" TO THE NORTH
- 9) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 22, 2011 FOR PROJECT NUMBER 10-WZ, THE REPLACEMENT OF BRIDGE 943.5-538.5 ON COUNTY ROAD "K5" NORTH OF COUNTY ROAD 70, **FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL** AT THE SOUTH 1/4 CORNER OF SECTION 34-20-11 ON THE 4TH STANDARD PARALLEL FROM MY TIES DATED JULY 10, 2001. THIS 5/8" CAPPED REBAR REPLACED A 5/8" REBAR THAT WAS SET BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN APRIL 1994 FOR HIS PROJECT NUMBER 94075-02 AFTER HE DEEMED THE CORNER LOST, AND HE RESET THIS CORNER ON TRUE LINE AND HALFWAY BETWEEN THE SOUTHWEST AND SOUTHEAST CORNERS OF SECTION 34-20-11 ON THE 4TH STANDARD PARALLEL.
- 1) 44.7' NW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 2) 53.2' NW TO THE TOP CENTER OF A CORNER FENCE POST FOR A CHAIN-LINK FENCE AT THE CEMETERY FOR FENCES NORTH & SOUTHWEST
 - 3) 63.7' NE TO A FOUND CONCRETE NAIL & WASHER IN A POWER POLE
 - 4) 67.1' ENE TO THE TOP CENTER OF A FIBER OPTIC TELEPHONE CABLE MARKER POST
 - 5) 52.0' SE TO THE TOP CENTER OF A CORNER FENCE POST FOR FENCES EAST, WEST AND SOUTH
 - 6) IN THE TRAVELED WAY OF ASPHALT COUNTY ROAD 70 EAST-WEST
 - 7) 8' EAST TO THE TRAVELED WAY OF ASPHALT COUNTY ROAD "K5" TO THE NORTH
- 10) RICHARD J. IMAN, L.S. 1450, OF BG CONSULTANTS, INC., IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 10, 2012 FOR PROJECT NUMBER 11-1308E, SAID THAT **HE FOUND A 5/8" LYON COUNTY CAPPED REBAR IN A MONUMENT BOX** AT THE SOUTH 1/4 CORNER OF SECTION 34-20-11 ON THE 4TH STANDARD PARALLEL USING REFERENCES FROM LYON COUNTY.
- 1) 63.7' NE TO A FOUND NAIL & SHINER IN A POWER POLE
 - 2) 44.6' NW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 3) ON THE TRAVEL WAY OF EAST-WEST ASPHALT ROAD [#70]
 - 4) 10' EAST TO THE TRAVEL WAY OF ASPHALT ROAD RUNNING NORTH [K-5]
- 11) BG CONSULTANTS, INC. PLANS FOR THE CITY OF OLPE 2013 WATERLINE IMPROVEMENTS DATED FEBRUARY 1, 2013 AND SIGNED BY BRIAN J. FOSTER, P.E., FOR PROJECT NUMBER 11-1308E, SHOWS THE FOLLOWING INFORMATION ON THE

SECTION CORNER SUMMARY ON SHEET NUMBER 3 FOR THE SOUTH 1/4 CORNER OF SECTION 34-20-11 ON THE 4TH STANDARD PARALLEL:

- 1) FOUND 5/8" REBAR W/ LYON COUNTY CAP IN A MONUMENT BOX
- 2) 63.7' NE TO A FOUND NAIL & SHINER IN A POWER POLE
- 3) 44.6' NW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 4) ON THE TRAVEL WAY OF EAST-WEST ASPHALT ROAD [#70]
- 5) 10' EAST TO THE TRAVEL WAY OF THE ASPHALT ROAD RUNNING NORTH [K-5]
- 6) COORDINATES: N = -1562.47 E = -2695.10

SOUTH QUARTER CORNER 34-20-11