

**WEST 1/16<sup>TH</sup> CORNER SOUTHWEST QUARTER OF SECTION 34, TOWNSHIP 20 SOUTH,  
RANGE 11 EAST**

- 1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED MARCH 9, 2007, FOR PROJECT NUMBER 07055-02, SURVEY F33002 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE EAST 990 FEET OF THE SOUTHEAST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 33-20-11 FOR FARM & HOME REALTY/WENDING FOR PROJECT NUMBER 07055-02 DATED MARCH 20, 2007, SHOWS ON HIS SURVEY DRAWING THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 33-20-11 TO BE ON LINE AND HALFWAY BETWEEN THE EAST 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 33-20-11, BUT THE POSITION WAS **NOT** MONUMENTED ON THIS SURVEY AS IT FALLS IN A DRAINAGE AREA.

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,278.27' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A **WITNESS CORNER**
- 2) 1,321.77' SOUTH TO THE 5/8" REBAR IN A MONUMENT WELL HE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-20-11
- 3) 1,321.76' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE NE1/4 OF THE SE1/4 OF SECTION 33-20-11
- 4) 3,965.29' NORTH TO THE 5/8" REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 33-20-11
- 5) 70.0' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A **WITNESS CORNER**
- 6) 990.00' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE EAST 990' OF THE SE1/4 OF THE SE1/4 OF SECTION 29-20-11
- 7) 1,323.39' WEST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 33-20-11
- 8) 2,646.78' WEST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 33-20-11

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 34-20-11