

**NORTH 1/4 CORNER SECTION 35, TOWNSHIP 20 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 389 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 19" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 35-20-11.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.95 CHAINS WEST TO THE 24" X 12" X 5" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-20-11
  - 2) 39.95 CHAINS EAST TO THE 29" X 17" X 2" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-20-11
  
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 264 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 6 TO 8 PETITIONED BY JAMES BROTT AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 20-11 [PACKET 498 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 14, 1884, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON APRIL 11, 1884 AS NOTED BY P. Y. HALLBERG, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MAY 17, 1884 BY ROLAND LARKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 35-20-11 ON THIS ROAD SURVEY.  
HIS SURVEY NOTES AND DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES AT 17 FEET NORTH AND 33 FEET SOUTH OF THE SECTION LINE FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-20-11; THEN CONTINUES WEST AT 25 FEET ON EACH SIDE OF THE SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-20-11; THEN NORTH ON THE SECTION LINES AT 10 FEET ON THE WEST SIDE AND 40 FEET ON THE EAST SIDE OF THE SECTION LINE, FOR 1/2 MILE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 27-20-11
  - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES AT 25 FEET ON EACH SIDE OF THE SECTION LINE FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 36-20-11 TO COMMENCE THIS ROAD SURVEY
  
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 7, 1989, FOR JOB NUMBER 89069, SAID THAT HE CONSIDERED THAT THE NORTH 1/4 CORNER OF SECTION 35-20-11 WAS **OBLITERATED. HE RESET THIS CORNER WITH A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE NORTH 1/4 CORNER OF SECTION 35-20-11.
  - 1) ON THE WEST SIDE OF A CORNER FENCE POST
  - 2) ON LINE WITH AN EAST-WEST FENCE TO THE EAST
  - 3) ON LINE WITH AN EAST-WEST FENCE TO THE WEST
  - 4) ON LINE WITH A NORTH-SOUTH FENCE TO THE SOUTH
  - 5) ON LINE WITH A NORTH-SOUTH FENCE TO THE NORTH
  
- 4) LLOYD J. DOBLER, L.S. 541, IN SURVEY F35027 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY FOR RAY SCHREINER DATED APRIL 11, 2000, SHOWS THAT **HE FOUND THE 1/2" IRON BAR WITH LYON COUNTY CAP** AT THE NORTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 35-20-11. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE BOOK.

NORTH QUARTER CORNER 35-20-11