

**NORTHWEST CORNER SECTION 36, TOWNSHIP 20 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 384 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 29" X 17" X 2"** FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-20-11.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.11 CHAINS EAST TO THE 22" X 12" X 3-1/2" SANDSTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 36-20-11
  - 2) 80.22 CHAINS EAST TO THE 22" X 15" X 5" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 25 & 36-20-11 ON THE EAST TOWNSHIP BOUNDARY
  
- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 25 DATED AUGUST 17, 1882, FOR A ROAD IN TOWNSHIP 20, RANGE 11 FOR LOUIS NELSON, THE PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 25-20-11 AT THE TERMINUS OF THIS ROAD SURVEY. THERE IS NO WIDTH RECORDED ON THIS SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 40.09 CHAINS TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER BETWEEN SECTION 25-20-11; THEN CONTINUES EAST ON THE SECTION LINES FOR 40.14 CHAINS TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 25-20-11 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY
  
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, A ROAD SURVEY FOR ROAD NUMBER 191 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 350 TO 352 PETITIONED BY LEWIS NELSON AND OTHERS FOR A COUNTY ROAD BETWEEN SECTIONS 25 & 36-20-11 [PACKET 404 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 17, 1882, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 10, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 25, 1882 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 25-20-11 AT THE TERMINUS OF THIS ROAD SURVEY.  
HIS NOTES SHOW THE FOLLOWING INFORMATION:
  - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 40.09 CHAINS TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER BETWEEN SECTION 25-20-11; THEN CONTINUES EAST ON THE SECTION LINES FOR 40.14 CHAINS TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 25-20-11 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY
  
- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 264 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 6 TO 8 PETITIONED BY JAMES BROTT AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 20-11 [PACKET 498 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 14, 1884, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON APRIL 11, 1884 AS NOTED BY P. Y. HALLBERG, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MAY 17, 1884 BY ROLAND LARKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 36-20-11 TO COMMENCE THIS ROAD SURVEY.  
HIS SURVEY NOTES AND DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES AT 25 FEET ON EACH SIDE OF THE SECTION LINE FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 35-20-11; THEN CONTINUES WEST ON THE SECTION LINES AT 17 FEET NORTH AND 33 FEET SOUTH OF THE SECTION LINE FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-

20-11; THEN CONTINUES WEST AT 25 FEET ON EACH SIDE OF THE SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-20-11; THEN NORTH ON THE SECTION LINES AT 10 FEET ON THE WEST SIDE AND 40 FEET ON THE EAST SIDE OF THE SECTION LINE, FOR 1/2 MILE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 27-20-11

- 5) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 36  
ON MARCH 5, 1948, A PETITION SIGNED BY BRAD BOLZ AND OTHERS FOR THE VACATION OF A ROAD IN TOWNSHIP 15-10 WAS PRESENTED TO GEORGE K. JACKSON, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS ON APRIL 5, 1948 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON APRIL 5, 1948 VACATED THE FOLLOWING ROAD:
- 1) BEGINNING AT THE SOUTHWEST CORNER OF SECTION 26-20-11; THENCE EAST ALONG THE SOUTH SIDE OF SAID SECTION 1 MILE AND ENDING THERE.
  - 2) THIS ROAD SHOULD BE VACATED.
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F25001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR PROJECT NUMBER 84133 DATED OCTOBER 24, 1984, SAID IN HIS *REPORT OF SURVEY* SAID THAT HE USED THE PHYSICAL EVIDENCE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 25-20-11 AS HE DID NOT LOCATE A MONUMENT AT THIS CORNER. THIS SURVEY WAS FILED IN VOLUME 411 ON PAGE 686 IN THE REGISTER OF DEEDS OFFICE ON OCTOBER 30, 1984.
- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 7, 1989, FOR JOB NUMBER 89069, SAID THAT HE DETERMINED THAT THE NORTHEAST CORNER OF SECTION 35-20-11 WAS OBLITERATED IN NORTH-SOUTH POSITION AND LOST IN EAST-WEST POSITION. **HE SET A 1" X 6" BOLT OVER A CONCRETE CULVERT FOR THE NORTHEAST CORNER OF SECTION 35-20-11.**
- 1) 57.45' SSE TO A PK NAIL & WASHER IN A CORNER FENCE POST
  - 2) 42.55' SSW TO A PK NAIL & WASHER IN A POWER POLE
  - 3) 28.05' WEST TO A PK NAIL & WASHER IN A CORNER FENCE POST
  - 4) 26.65' SE TO THE NEAR EDGE OF A CONCRETE BOX CULVERT
  - 5) 19.05' NW TO THE NEAR EDGE OF A CONCRETE BOX CULVERT
  - 6) IN THE CENTERLINE TRAVELED WAY OF THE COUNTY ROAD EAST-WEST
  - 7) 1.0' WEST TO THE CENTERLINE TRAVELED WAY OF THE COUNTY ROAD NORTH-SOUTH

NORTHWEST CORNER 36-20-11