

**SOUTH 1/4 CORNER SECTION 36, TOWNSHIP 20 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 18 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE ROCK 22" X 13" X 2"** IN THE EDGE OF TIMBER FOR THE SOUTH 1/4 CORNER SECTION 36-20-11 ON THE 4<sup>TH</sup> STANDARD PARALLEL ON NOVEMBER 18, 1855, FROM WHICH:
  - 1) A BURR OAK TREE 20" IN DIAMETER BEARS N. 58° E. AT 48 LINKS DISTANCE
  - 2) A BURR OAK TREE 13" IN DIAMETER BEARS S. 22-1/2° E. AT 79 LINKS DISTANCE

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

  - 1) 40.00 CHAINS WEST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 21" X 9" X 3" LIMESTONE THEY SET ON A SLOPE TO THE SOUTH FOR THE CORNER TO SECTIONS 35 & 36-20-11
  - 2) 40.00 CHAINS EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 18" X 10" X 4" LIMESTONE THEY SET IN THE BOTTOM OF THE PRAIRIE FOR THE CORNER TO TOWNSHIP 20 SOUTH, RANGES 11 & 12 EAST
  
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 123 RECORDED IN SURVEY BOOK "A" ON PAGES 210 & 211 DATED MAY 31, 1869 FOR A SURVEY OF LAND SITUATED IN SECTION 36-20-11, TO SURVEY THE NORTH 1/2 OF THE SOUTHWEST 1/4, AND THE NORTH 1/2 OF THE SOUTHEAST 1/4, AND ALSO THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SAID SECTION 36, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 36-20-11 ON THE 4<sup>TH</sup> STANDARD PARALLEL ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

  - 1) 159 RODS, 8 LINKS WEST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 36-20-11
  - 2) 79 RODS, 1-1/2 LINKS NORTH TO THE STONE HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF THE SW1/4 OF SECTION 36-20-11
  - 3) 158 RODS, 3 LINKS NORTH TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 36-20-11

SOUTH QUARTER CORNER 36-20-11