

**WEST 1/16<sup>TH</sup> CORNER SOUTHWEST QUARTER OF SECTION 36, TOWNSHIP 20 SOUTH,  
RANGE 11 EAST**

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 123 RECORDED IN SURVEY BOOK "A" ON PAGES 210 & 211 DATED MAY 31, 1869 FOR A SURVEY OF LAND SITUATED IN SECTION 26-20-11, TO SURVEY THE NORTH 1/2 OF THE SOUTHWEST 1/4, AND THE NORTH 1/2 OF THE SOUTHEAST 1/4, AND ALSO THE SOUTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 36, SAID THAT **HE SET A STONE** FOR THE WEST 1/2/4 CORNER OF THE SOUTHWEST 1/4 OF SECTION 36-20-11 EQUIDISTANT BETWEEN THE STONES THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 36-20-11 AND THE SOUTHWEST CORNER OF SECTION 36-20-11 ON THE 4<sup>TH</sup> STANDARD PARALLEL ON THIS SURVEY.

**HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:**

- 1) 159 RODS, 8 LINKS EAST TO THE STONE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF THE SW1/4 OF SECTION 36-20-11
- 2) LLOYD J. DOBLER, L.S. 541, IN SURVEY F36001 IN THE SURVEY FILES FOR TOWNSHIP 20-11 FOR A SURVEY OF A 1.00 ACRE TRACT IN THE SOUTHWEST QUARTER OF SECTION 36-20-11 FOR TIMOTHY BLUMA DATED JULY 19, 1978, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A 1/2" IRON PIN** AT THE SOUTHWEST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 36-20-11 ON LINE AND EQUAL DISTANCE BETWEEN THE WEST 1/4 CORNER OF SECTION 36-20-11 AND THE SOUTHWEST CORNER OF SECTION 36-20-11 ON THE 4<sup>TH</sup> STANDARD PARALLEL. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES. THIS CORNER IS ALSO THE SOUTHWEST CORNER OF THE 1.00 ACRE TRACT.

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 208.71' NORTH TO THE 1/2" IRON PIN HE SET FOR THE NORTHWEST CORNER OF THE 1.00 ACRE TRACT AND WITNESSED BY THE 1/2" IRON PIN HE SET AT 25' EAST ON THE EAST ROAD RIGHT-OF-WAY LINE
- 2) 1,316.57' NORTH TO THE "MONUMENT" AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 36-20-11 – NOT DESCRIBED
- 3) 1,316.57' SOUTH TO THE "MONUMENT" AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 36-20-11 ON THE 4<sup>TH</sup> STANDARD PARALLEL – NOT DESCRIBED
- 4) 25' EAST TO THE 1/2" IRON PIN HE SET ON THE EAST ROAD RIGHT-OF-WAY LINE
- 5) 208.71' EAST TO THE 1/2" IRON PIN HE SET FOR THE SOUTHEAST CORNER OF THE 1.00 ACRE TRACT

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 36-20-11