

NORTH 1/4 CORNER SECTION 02, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) ON PAGE 62 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 17" X 11" X 4"** FOR THE NORTH 1/4 CORNER OF SECTION 2-20-12 ON THE TOWNSHIP LINE ON DECEMBER 5, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 21" X 11" X 5" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 2 & 3-20-12
- 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 24" X 12" X 2" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 1 & 2-20-12

- 2) JOHN E. TAYLOR, L.S. 713, OF TAYLOR SURVEYING CORPORATION, P.A., IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 21, 1996, FOR JOB NUMBER 8446, LARGE SURVEY SR #35001 IN THE SURVEY DRAWER FOR TOWNSHIP 19-12, SAID THAT HE SEARCHED FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 35-19-12 ON THE TOWNSHIP LINE WITH A COUNTY BACKHOE, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST**. **HE SET A 1/2" IRON BAR WITH HIS "LS 713" CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 35-19-12 ON THE TOWNSHIP LINE AT HALFWAY BETWEEN THE EXISTING CORNERS AT THE SOUTHWEST AND SOUTHEAST CORNERS OF SECTION 35-19-12.

- 1) 30.0' NORTH TO A 1" IRON BAR ON THE RIGHT-OF-WAY LINE
- 2) 22.15' SSW TO A 60 D SPIKE & SHINER IN A 10" HACKBERRY TREE
- 3) 46.4' SE TO A 60 D SPIKE & SHINER IN A 4" HACKBERRY TREE
- 4) 93.9' ENE TO A 60 D SPIKE & SHINER IN A 24" LOCUST TREE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,638.74' WEST ON THE TOWNSHIP LINE TO THE IRON PIN HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 35-19-12
- 2) 2,638.74' EAST ON THE TOWNSHIP LINE TO THE IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 35-19-12
- 3) 2,653.27' NORTH TO THE 1/2" REBAR WITH HIS "LS 713" CAP HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 35-19-12
- 4) 5,306.54' NORTH TO THE 1/2" REBAR WITH HIS "LS 713" CAP HE SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 35-19-12

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 15, 2006, FOR PROJECT NUMBER 06064-02, SURVEY F35001 IN THE SURVEY FILE FOR TOWNSHIP 19-12 AND SURVEY F02001 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR A SURVEY OF THE WEST 66 ACRES OF THE NORTH 110 ACRES OF THE SOUTHWEST QUARTER OF SECTION 35-19-12 AND ALSO THE NORTH 83 ACRES OF THE NORTHWEST QUARTER OF SECTION 2-20-12 FOR WELLNITZ, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE SOUTH 1/4 CORNER OF SECTION 35-19-12 ON THE TOWNSHIP LINE FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE BY JOHN E. TAYLOR, LS 713, AND DATED 1996.

- 1) 30.0' NORTH TO A 1" IRON BAR
- 2) 33.2' SSW TO A 60 D SPIKE & SHINER IN A 10" HACKBERRY TREE
- 3) 46.4' SE TO A 40 D SPIKE & SHINER IN A 14" HACKBERRY TREE
- 4) 93.9' ENE TO A 60 D SPIKE & SHINER IN A 24" HACKBERRY TREE
- 5) 2.5' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 130 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,638.65' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 35-19-12

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 2,638.77' EAST ON THE TOWNSHIP LINE TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 2-10-12
- 3) 1,365.96' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET
- 4) 2,721.92' SOUTH TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 2-20-12
- 5) 5,374.82' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 2-20-12

NORTH QUARTER CORNER 02-20-12