

CENTER CORNER OF SECTION 04, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 84 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 141 DATED SEPTEMBER 8, 1875 TO SUBDIVIDE THE SOUTHWEST 1/4 OF SECTION 4-20-12, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 4-20-12 THAT WAS SET ON SEPTEMBER 5, 1870 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,323' SOUTH TO THE 18" X 14" X 2" STONE HE SET IN A DRY RAVINE FOR THE PERMANENT EAST 1/2/4 CORNER OF THE SW1/4 OF SECTION 4-20-12
 - 2) 2,646' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 4-20-12

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 109 RECORDED IN SURVEY BOOK "F" ON PAGE 94 DATED APRIL 21 & 22, 1886, REQUESTED BY JOHN REIGLIN TO ESTABLISH THE LINES AND CORNERS OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 4-20-12, SAID THAT **HE SET A 16" X 4" X 3" STONE MARKED WITH A "+" ON THE TOP** AT THE INTERSECTION OF THE LINES BETWEEN THE 1/4 CORNERS FOR THE CENTER CORNER OF SECTION 4-20-12.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,314.9' SOUTH TO THE 26" X 16" X 2" STONE MARKED "1/8" ON THE WEST FACE HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE SW1/4 OF SECTION 4-20-12
 - 2) 2,629.8' SOUTH TO THE SMALL STONE PIECES HE FOUND IN THE GROUND AT THE SOUTH 1/4 CORNER OF SECTION 4-20-12

- 3) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A ROAD SURVEY FOR ROAD NUMBER 697 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 54 PETITIONED BY JAMES W. VANCLEVE AND OTHERS FOR A ROAD IN TOWNSHIP 20-12 [PACKET 788 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND THE COUNTY SURVEYOR ON AUGUST FEBRUARY 8, 1915 AND WAS ORDERED THAT THE ROAD BE GRANTED BEGINNING AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 4-20-12, THENCE NORTH ON THE SECTION LINES 3/4 MILES TO THE NORTHWEST CORNER OF SAID SECTION 3-20-12 AND ENDING THERE, SAID ROAD TO BE 40 FEET WIDE, 20 FEET EACH SIDE OF THE SECTION LINE. ON SEPTEMBER 10, 1915 AS NOTED BY E. MOORHEAD, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, SHOWS ON THE *RETURN OF SURVEY AND PLAT* THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 4-20-12. THIS CORNER WAS NOT A PART OF THE ROAD ON THIS ROAD SURVEY, BUT WAS APPARENTLY USED TO LOCATE THE SECTION LINE BETWEEN SECTIONS 4 AND 5-20-12. THIS ROAD WAS RECORDED ON JANUARY 1, 1916 BY W. S. RUGGLES, COUNTY SURVEYOR.

CENTER CORNER 04-20-12