

**NORTH 1/4 CORNER SECTION 08, TOWNSHIP 20 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 566 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 15" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 8-20-12, FROM WHICH:
  - 1) A BURR OAK TREE 40" IN DIAMETER BEARS NORTH AT 7 LINKS DISTANCE
  - 2) A HICKORY TREE 7" IN DIAMETER BEARS S. 52° E. AT 47 LINKS DISTANCE

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

  - 1) 39.93 CHAINS WEST TO THE 36" X 12" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-20-12
  - 2) 39.93 CHAINS EAST TO THE 24" X 15" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-20-12
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 83 OF THE 8<sup>TH</sup> TERM, A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON PAGE 140 DATED SEPTEMBER 7, 1875 TO SURVEY A COUNTY ROAD PETITIONED FOR BY M. MYERS, ET. AL., IN TOWNSHIP 20, RANGE 12, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 8-20-12 ON THIS ROAD SURVEY.
  
- 3) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 20-12 SHOWING THE RESULTS OF A SURVEY OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 5-20-12 DATED SEPTEMBER 15, 1975, SHOWS ON HIS SURVEY DRAWING THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE SOUTH 1/4 CORNER OF SECTION 5-20-12 TO BE ON LINE AND HALFWAY BETWEEN THE "MONUMENTS" AT THE SOUTHEAST CORNER AND THE SOUTHWEST CORNER OF SECTION 5-20-12, BUT THE POSITION WAS **NOT** MONUMENTED ON THIS SURVEY.

HIS DRAWING SHOWS THE FOLLOWING INFORMATION:

  - 1) 2,638' WEST TO THE "MONUMENT" AT THE SOUTHWEST CORNER OF SECTION 5-20-12 – NOT DESCRIBED
  - 2) 2,638' EAST TO THE "MONUMENT" AT THE SOUTHEAST CORNER OF SECTION 5-20-12 – NOT DESCRIBED
  - 3) 2,640' NORTH TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 5-20-12
  
- 4) MARION WAYNE BLACKBOURN, L.S. 1127, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 27, 1994, FOR JOB NUMBER 93-12-054, LARGE SURVEY SR #05001 IN THE SURVEY DRAWER FOR TOWNSHIP 20-12, SAID THAT HE SEARCHED FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 5-20-12, BUT HE DID **NOT** FIND THE STONE. HE FOUND NOTES FROM THE LYON COUNTY ROAD RECORDS STATING THERE WAS AN IRON PIN SET FOR THIS LOCATION, BUT THE PIN AND REFERENCES WERE **NOT** FOUND AS PER THE NOTES IN ROAD PROFILE "1935". HE CONSIDERED THAT **THIS CORNER WAS LOST. HE DETERMINED A CALCULATED POSITION** FOR THE SOUTH 1/4 CORNER OF SECTION 5-20-12 TO BE ON TRUE LINE AND HALFWAY BETWEEN THE SOUTHWEST CORNER AND THE SOUTHEAST CORNER OF SECTION 5-20-12, BUT THE POSITION WAS **NOT** MONUMENTED ON THIS SURVEY.

HIS DRAWING SHOWS THE FOLLOWING INFORMATION:

  - 1) 2,638.00' WEST TO THE SOUTHWEST CORNER OF SECTION 5-20-12 – NOT DESCRIBED
  - 2) 2,638.00' EAST TO THE SOUTHEAST CORNER OF SECTION 5-20-12 – NOT DESCRIBED

NORTH QUARTER CORNER 08-20-12