

**WEST 1/4 CORNER SECTION 08, TOWNSHIP 20 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 565 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 7 & 8-20-12.
  
- 2) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR COUNTY ROAD NUMBER 647 RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 49 AT THE REQUEST OF OWEN HUGHES, PRINCIPAL PETITIONER, FOR A COUNTY ROAD IN TOWNSHIP 20-12, SAID THAT HE TERMINATED THE CENTERLINE OF THE FIRST ROAD OF THIS ROAD SURVEY AT A POINT 2,658 FEET NORTH OF THE SOUTHEAST CORNER OF SECTION 7-20-12 AND APPARENTLY 20 FEET NORTH OF THE EAST 1/4 CORNER OF SECTION 7-20-12. HE DID NOT DESCRIBE ANY MONUMENT AT THIS CORNER. THIS ROAD WAS SURVEYED JANUARY 19, 1910 AND ENTERED ON JANUARY 20, 1910. HE NOTED IN THE UPPER RIGHT CORNER THAT THIS ROAD SURVEY IS RECORDED IN ROAD RECORD BOOK "E" ON PAGE 4.  
HIS SURVEY NOTES THE FOLLOWING INFORMATION:
  - 1) THE CENTERLINE OF THE FIRST ROAD ON THIS ROAD SURVEY EXTENDS SOUTH ON THE SECTION LINE FOR 2,658' TO THE SOUTHEAST CORNER OF SECTION 7-20-12 AND THE BEGINNING OF THE FIRST ROAD ON THIS ROAD SURVEY
  - 2) THIS POINT IS ALSO THE TERMINATION OF THE CENTERLINE OF THE SECOND ROAD ON THIS ROAD SURVEY THAT EXTENDS WEST FOR 1,315 FEET TO THE POINT OF BEGINNING OF THE THIRD ROAD ON THIS ROAD SURVEY THAT EXTENDS NORTH ON THE 1/4 SECTION LINE, THEN CONTINUES WEST FOR AN ADDITIONAL 3,948 FEET TO A POINT 20 FEET NORTH OF THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 7-20-12 ON THE RANGE LINE
  
- 3) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 647 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 4 PETITIONED BY OWEN HUGHES AND OTHERS FOR THE LOCATION AND VACATION OF ROADS IN TOWNSHIP 20-12 [PACKET 760 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JULY 14, 1909 AND WAS ALLOWED ON OCTOBER 8, 1909 AS NOTED BY ELI FOWLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, SAID THAT HE TERMINATED THE CENTERLINE OF THE FIRST ROAD OF THIS ROAD SURVEY AT A POINT 2,658 FEET NORTH OF THE SOUTHEAST CORNER OF SECTION 7-20-12 AND APPARENTLY 20 FEET NORTH OF THE EAST 1/4 CORNER OF SECTION 7-20-12. HE DID NOT DESCRIBE ANY MONUMENT AT THIS CORNER. THIS ROAD WAS SURVEYED JANUARY 19, 1910 AND ENTERED ON JANUARY 20, 1910. HE NOTED IN THE UPPER RIGHT CORNER THAT THIS ROAD SURVEY IS RECORDED IN ROAD RECORD BOOK "E" ON PAGE 4.  
HIS SURVEY NOTES THE FOLLOWING INFORMATION:
  - 1) THE CENTERLINE OF THE FIRST ROAD ON THIS ROAD SURVEY EXTENDS SOUTH ON THE SECTION LINE FOR 2,658' TO THE SOUTHEAST CORNER OF SECTION 7-20-12 AND THE BEGINNING OF THE FIRST ROAD ON THIS ROAD SURVEY
  - 2) THIS POINT IS ALSO THE TERMINATION OF THE CENTERLINE OF THE SECOND ROAD ON THIS ROAD SURVEY THAT EXTENDS WEST FOR 1,315 FEET TO THE POINT OF BEGINNING OF THE THIRD ROAD ON THIS ROAD SURVEY THAT EXTENDS NORTH ON THE 1/4 SECTION LINE, THEN CONTINUES WEST FOR AN ADDITIONAL 3,948 FEET TO A POINT 20 FEET NORTH OF THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 7-20-12 ON THE RANGE LINE

CONTINUED ON PAGE 2

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR THE SURVEY OF A 13.9 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 7-20-12 FOR RALPH VANSICKLE DATED NOVEMBER 1, 2007 FOR PROJECT NUMBER 07362-02, SHOWS ON HIS SURVEY DRAWING THAT **HE DETERMINED A THEORETICAL POSITION** FOR THE EAST 1/4 CORNER OF SECTION 7-20-12 TO BE ON LINE AND HALFWAY BETWEEN THE NORTHEAST CORNER AND THE SOUTHEAST CORNER OF SECTION 7-20-12. HE DID **NOT** MONUMENT THE THEORETICAL POSITION ON THIS SURVEY. **HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 2,640.90' NORTH TO THE 1/2" REBAR AND STONE HE FOUND AT THE NORTHEAST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 7-20-12
  - 2) 2,640.90' SOUTH TO THE 1/2" X 15" PIPE WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 7-20-12
  - 3) 5,281.81' SOUTH TO THE 1/2" REBAR WITH "LS 1127" CAP HE FOUND AT THE SOUTH-EAST CORNER OF THE NE1/4 OF SECTION 18-20-12
  - 4) 1,321.50' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 7-20-12
  - 5) 2,643.00' WEST TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 7-20-12
  - 6) 5,262.64' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 7-20-12 ON THE RANGE LINE

WEST QUARTER CORNER 08-20-12