

NORTH 1/4 CORNER SECTION 09, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) ON PAGE 560 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 25" X 11" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 9-20-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.93 CHAINS WEST TO THE 24" X 15" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-20-12
 - 2) 39.93 CHAINS EAST TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-20-12

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 84 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 141 DATED SEPTEMBER 8, 1875 TO SUBDIVIDE THE SOUTHWEST 1/4 OF SECTION 4-20-12, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 4-20-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,323' NORTH TO THE 18" X 14" X 2" STONE HE SET IN A DRY RAVINE FOR THE PERMANENT EAST 1/2/4 CORNER OF THE SW1/4 OF SECTION 4-20-12
 - 2) 2,646' NORTH TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 4-20-12

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 109 RECORDED IN SURVEY BOOK "F" ON PAGE 94 DATED APRIL 21 & 22, 1886, REQUESTED BY JOHN REIGLIN TO ESTABLISH THE LINES AND CORNERS OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 4, SAID THAT **HE FOUND SMALL PIECES OF STONE IN THE GROUND** AT THE SOUTH 1/4 CORNER OF SECTION 4-20-12 ON THIS SURVEY. HE DID NOT SAY IF HE SET A NEW STONE FOR THIS CORNER.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,314.19' NORTH TO THE 26" X 16" X 2" STONE MARKED "1/8" ON THE WEST FACE HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE SW1/4 OF SECTION 4-20-12
 - 2) 2,629.8' NORTH TO THE 16" X 14" X 3" STONE MARKED WITH A "+" ON TOP HE SET FOR THE CENTER CORNER OF SECTION 4-20-12

NORTH QUARTER CORNER 09-20-12