

WEST 1/4 CORNER SECTION 14, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) ON PAGE 551 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 13" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 14 & 15-20-12.

- 2) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN **LEGAL SURVEY SR #15001** IN THE LARGE SURVEY DRAWER FOR TOWNSHIPS 20-10 TO 20-13 DATED APRIL 13, 1956, SHOWS AN **IRON PIN** AT THE WEST 1/4 CORNER OF SECTION 14-20-12 ON THIS **LEGAL SURVEY**. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE BOOKS.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,640.23' SOUTH TO THE COMPUTED LOCATION FOR THE SOUTHEAST CORNER OF SECTION 15-20-12
 - 2) 7,920.69' SOUTH TO THE CORNER STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 22-20-12
 - 2) 2,640.23' NORTH TO THE COMPUTED LOCATION FOR THE NORTHEAST CORNER OF SECTION 15-20-12
 - 3) 7,920.69' NORTH TO THE COMPUTED LOCATION FOR THE NORTHEAST CORNER OF SECTION 10-20-12
 - 3) 10,560.92' NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 3-20-12

- 3) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK NUMBER 2 ON PAGE 18 AT THE REQUEST OF D. D. DANFORD TO LOCATE AND PERMANENTLY ESTABLISH THE LINE BETWEEN THE NORTH 1/2 AND THE SOUTH 1/2 OF SECTION 15-20-12 THAT BEGAN ON APRIL 13, 1956 AND WAS COMPLETED ON APRIL 16, 1956, SAID THAT HE DID **NOT** FIND THE STONE AT THE EAST 1/4 CORNER OF SECTION 15-20-12. **HE SET AN IRON PIN** FOR THE EAST 1/4 CORNER OF SECTION 15-20-12 ON LINE AND AT A PRORATED DISTANCE BETWEEN THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 3-20-12 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 22-20-12, AND IN THE APPARENT CENTER OF THE ROAD ON THIS **PERMANENT SURVEY**. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 4) 2,640.23' SOUTH TO THE COMPUTED LOCATION FOR THE SOUTHEAST CORNER OF SECTION 15-20-12
 - 5) 7,920.69' SOUTH TO THE CORNER STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 22-20-12
 - 2) 2,640.23' NORTH TO THE COMPUTED LOCATION FOR THE NORTHEAST CORNER OF SECTION 15-20-12
 - 3) 7,920.69' NORTH TO THE COMPUTED LOCATION FOR THE NORTHEAST CORNER OF SECTION 10-20-12
 - 6) 10,560.92' NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 3-20-12

WEST QUARTER CORNER 14-20-12