

NORTH 1/16TH CORNER OF THE NORTHWEST QUARTER OF SECTION 16, TOWNSHIP 20 SOUTH, RANGE 12 EAST

1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED MAY 10, 2008 FOR PROJECT NUMBER 08140-02, SURVEY F16001 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR THE SURVEY OF THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 16-20-12 FOR JOE BIGGS, SAID THAT **HE SET A 1/2" REBAR WITH HIS "LS 752" CAP** FOR THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 16-210-12 ON TRUE LINE AND HALFWAY BETWEEN THE NORTH QUARTER CORNER AND THE NORTHWEST CORNER OF SECTION 16-20-12.

- 1) 1.0' EAST TO A LINE OF FENCE TO THE SOUTH
- 2) 6.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 110 EAST-WEST
- 3) 30.30' ENE TO A 40 D SPIKE & WASHER IN A STEEL FENCE POST
- 4) 24.90' NORTH TO A 40 D SPIKE & WASHER IN A STEEL FENCE POST
- 5) 23.90' NNW TO A 40 D SPIKE & WASHER IN A STEEL FENCE POST
- 6) 23.15' SSE TO A CONCRETE NAIL & WASHER IN A HEDGE FENCE POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,317.26' WEST TO THE SQUARE 3/4" IRON PIN HE FOUND AT THE NORTHWEST CORNER OF SECTION 16-20-12
- 2) 1,317.25' EAST TO THE 4" X 18" X 14" LIMESTONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 16-20-12
- 3) 3,956.41' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND OVER THE STONE AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 16-20-12
- 4) 1,323.58' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 16-20-12
- 5) 2,647.17' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 16-20-12

2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED NOVEMBER 18, 2008 FOR PROJECT NUMBER 08311-02, SURVEY F16002 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR A SURVEY OF THE WEST 410 FEET OF THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 16-20-12 FOR DAVID SCHMIDT, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS "LS 752" CAP** AT THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 16-20-12 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED MAY 2008.

- 1) 1.0' EAST TO A LINE OF FENCE TO THE SOUTH
- 2) 6.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 110 EAST-WEST
- 3) 30.30' ENE TO A 40 D SPIKE & WASHER IN A STEEL FENCE POST
- 4) 24.90' NORTH TO A 40 D SPIKE & WASHER IN A STEEL FENCE POST
- 5) 23.90' NNW TO A 40 D SPIKE & WASHER IN A STEEL FENCE POST
- 6) 23.15' SSE TO A CONCRETE NAIL & WASHER IN A HEDGE FENCE POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,317.26' WEST TO THE 3/4" SQUARE IRON PIN HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 16-20-12
- 2) 1,323.58' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE SOUTHEAST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 16-20-12

NORTH SIXTEENTH CORNER NORTHWEST QUARTER 16-20-12