

WEST 1/4 CORNER SECTION 17, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) ON PAGE 564 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 25" X 15" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 17 & 18-20-12.

- 2) MARION WAYNE BLACKBOURN, L.S. 1127, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 13, 1995, FOR PROJECT NUMBER 95-03-050, SURVEY F18001 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR THE SURVEY OF THE SOUTHWEST QUARTER OF SECTION 18-20-12 FOR DON HAGGMAN, RECORDED IN VOLUME 493 ON PAGE 167 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 1, 1995, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE EAST 1/4 CORNER OF SECTION 18-20-12, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 1/2" REBAR WITH HIS "LS 1127" CAP** FOR THE EAST 1/4 CORNER OF SECTION 18-20-12 BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER AND THE COUNTY ROAD RECORDS.
 - 1) 21.5' EAST TO A FENCE LINE NORTH-SOUTH
 - 2) 23.45' ENE TO A GATE POST
 - 3) 20.2' WEST TO A FENCE LINE NORTH-SOUTH
 - 4) 26.4' WSW TO A GATE POST
 - 5) IN THE CENTERLINE TRAVELED WAY OF THE COUNTY DIRT ROAD

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,643.62' WEST TO THE 1/2" REBAR WITH HIS "LS 1127" CAP HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 18-20-12
 - 2) 5,264.16' WEST TO THE 1/2" REBAR WITH HIS "LS 1127" CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 18-20-12 ON THE RANGE LINE
 - 3) 2,643.02' SOUTH TO THE 1/2" REBAR WITH HIS "LS 1127" CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 18-20-12
 - 4) 5,286.04' SOUTH TO THE 1/2" REBAR OF UNCERTAIN ORIGIN HE FOUND AT THE EAST 1/4 CORNER OF SECTION 19-20-12

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 25, 2007, FOR PROJECT NUMBER 07362-02, SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR THE SURVEY OF A 13.9 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 7-20-12 FOR RALPH VANSICKLE, SAID THAT **HE FOUND THE 1/2" REBAR WITH THE "LS 1127" CAP** AT THE EAST 1/4 CORNER OF SECTION 18-20-12 FROM EXISTING REFERENCE TIES FROM MARION WAYNE BLACKBOURN, L.S. 1127, DEPUTY COUNTY SURVEYOR, SURVEY IN SECTION 18-20-12 FOUND IN THE COUNTY ENGINEER'S OFFICE.
 - 1) 20.0' EAST TO A FENCE NORTH-SOUTH
 - 2) 28.7' ENE TO A CONCRETE NAIL & WASHER IN A GATE POST
 - 3) 32.5' SW TO A CONCRETE NAIL & WASHER IN A BRACE POST
 - 4) 23.0' SE TO A CONCRETE NAIL & WASHER IN A BRACE POST
 - 5) IN LINE WITH A FENCE TO THE EAST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,640.91' NORTH TO THE 1/2" PIPE WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 7-20-12
 - 2) 5,281.81' NORTH TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 7-20-12
 - 3) 7,922.71' NORTH TO THE 1/2" REBAR AND STONE HE FOUND AT THE NORTHEAST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 7-20-12

WEST QUARTER CORNER 17-20-12