

NORTH 1/4 CORNER SECTION 19, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) ON PAGE 564 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 18 & 19-20-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.74 CHAINS WEST TO THE 15" X 12" X 4" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 18 & 19-20-12 ON THE WEST TOWNSHIP BOUNDARY
 - 2) 40.00 CHAINS EAST TO THE 22" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-20-12

- 2) MARION WAYNE BLACKBOURN, L.S. 1127, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 13, 1995, FOR PROJECT NUMBER 95-03-050, SURVEY F18001 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR THE SURVEY OF THE SOUTHWEST QUARTER OF SECTION 18-20-12 FOR DON HAGGMAN, RECORDED IN VOLUME 493 ON PAGE 167 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 1, 1995, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 18-20-12, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 1/2" X 24" REBAR WITH HIS "LS 1127" CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 18-20-12 BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER AND USING PROPORTIONATE MEASUREMENT.
 - 1) 38.3' NW TO A NAIL IN A FENCE POST
 - 2) 115.3' WNW TO A GAS PIPELINE MARKER POST
 - 3) 75.9' ESE TO A GAS PIPELINE MARKER POST
 - 4) 25.0' NORTH TO AN IRON PIN SET AT THE EAST-WEST WIRE FENCE
 - 5) 4.8' SOUTH OF THE CENTERLINE TRAVELED WAY OF THE COUNTY GRAVEL ROAD EAST-WESTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,621.87' WEST TO THE 1/2" REBAR WITH HIS "LS 1127" CAP HE SET FOR THE SOUTHWEST CORNER OF SECTION 18-20-12 ON THE RANGE LINE
 - 2) 2,640.26' NORTH TO THE 1/2" REBAR WITH HIS "LS 1127" CAP HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 18-20-12
 - 3) 5,277.32' NORTH TO THE GLO STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 18-20-12
 - 4) 2,639.03' EAST TO THE 1/2" REBAR WITH HIS "LS 1127" CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 18-20-12

NORTH QUARTER CORNER 19-20-12