

**NORTH 1/4 CORNER SECTION 20, TOWNSHIP 20 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 564 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 15" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 17 & 20-20-12.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS WEST TO THE 22" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-20-12
  - 2) 40.00 CHAINS EAST TO THE 20" X 13" X 3-1/2" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-20-12
  
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 152, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 152 DATED NOVEMBER 22 & 23, 1886 ORDERED BY H. F. LAMB TO LOCATE THE LINES AND CORNERS TO THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 20-20-12, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 20-20-12 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,317' WEST TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE WEST 1/2 OF THE NW1/4 OF SECTION 20-20-12
  - 2) 2,634' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 20-20-12

NORTH QUARTER CORNER 20-20-12