

**NORTHWEST CORNER SECTION 20, TOWNSHIP 20 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 563 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 16" X 3"** FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-20-12.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST TO THE 20" X 15" X 2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 17 & 20-20-12
- 2) 80.00 CHAINS EAST TO THE 20" X 13" X 3-1/2" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-20-12

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 152, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 152 DATED NOVEMBER 22 & 23, 1886 ORDERED BY H. F. LAMB TO LOCATE THE LINES AND CORNERS TO THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 20-20-12, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 20-20-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,317' EAST TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 20-20-12
- 2) 2,634' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 20-20-12

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 271 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 34 TO 36 PETITIONED BY HUGH ROBERTS AND OTHERS FOR THREE ROADS IN TOWNSHIP 20-12 [PACKET 515 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 15, 1884, WAS ESTABLISHED AS A 40 FOOT WIDE NORTH-SOUTH AND 50 FOOT WIDE EAST-WEST ROADS ON JULY 15, 1884, AS NOTED BY P. Y. HALLBERG, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON NOVEMBER 20, 1884 BY ROLAND LAKIN, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 19-20-12 ON THE FIRST ROAD ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS FIRST ROAD EXTENDS NORTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 18-20-12 AT THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY
- 2) THIS FIRST ROAD EXTENDS SOUTH ON THE SECTION LINES TO AN ANGLE STONE HE SET IN THE NE/4 OF SECTION 32-20-12; THEN GOES THROUGH 3 ANGLE STONES TO A POINT 188 FEET EAST OF THE EAST 1/4 CORNER OF SECTION 31-20-12; THEN WEST 188 FEET TO THE EAST 1/4 CORNER OF SECTION 31-20-12 TO BEGIN THE FIRST ROAD ON THIS ROAD SURVEY

- 4) NATHANIEL BROWN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 379 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 462 TO 464 PETITIONED BY WILLIAM JULIAN AND OTHERS FOR A ROAD IN TOWNSHIP 20-12 [PACKET 628 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 10, 1891, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD, 25 FEET ON EACH SIDE OF THE SECTION LINE, ON OCTOBER 9, 1891 AS NOTED BY J. W. LAY, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON DECEMBER 16, 1891 BY C. W. WILHITE, COUNTY CLERK, SAID THAT **HE SET A ROAD STONE MARKED "R/1M"** AT THE SOUTHWEST CORNER OF SECTION 17-20-12 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE ROAD STONE MARKED "R/2M" HE SET FOR THE SOUTHWEST CORNER OF SECTION 18-20-12 ON THE RANGE LINE AT THE TERMINUS OF THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 1 MILE TO THE ROAD STONE MARKED "R" HE SET AT THE SOUTHWEST CORNER OF SECTION 16-20-12 TO BEGIN THIS ROAD SURVEY
- 5) MARION WAYNE BLACKBOURN, L.S. 1127, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 13, 1995, FOR PROJECT NUMBER 95-03-050, SURVEY F18001 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR THE SURVEY OF THE SOUTHWEST QUARTER OF SECTION 18-20-12 FOR DON HAGGMAN, RECORDED IN VOLUME 493 ON PAGE 167 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 1, 1995, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE SOUTHEAST CORNER OF SECTION 18-20-12, BUT THAT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. HE SET A 1/2" X 24" REBAR WITH HIS "LS 1127" CAP FOR THE SOUTHEAST CORNER OF SECTION 18-20-12 BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER AND BY PROPORTIONATE MEASUREMENT.
- 1) 13.2' WEST OF THE PROJECTED SOUTH FENCE LINE
  - 2) 13.2' WEST OF THE PROJECTED NORTH FENCE LINE
  - 3) 18.7' NORTH OF THE PROJECTED SOUTH FENCE LINE
  - 4) 26.7' NE TO A FENCE CORNER
  - 5) 43.3' SW TO A FENCE CORNER
  - 6) 25.1' SE TO A FENCE CORNER
  - 7) 6.0' EAST OF THE NORTH-SOUTH TRAVELED WAY OF THE GRAVEL ROAD
  - 8) 1.1' SOUTH OF THE EAST-WEST TRAVELED WAY OF THE GRAVEL ROAD
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION
- 1) 2,634.02' NORTH TO THE 1/2" REBAR WITH HIS "LS 1127" CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 18-20-12
  - 2) 2,639.03' WEST TO THE 1/2" REBAR WITH HIS "LS 1127" CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 18-20-12
  - 3) 5,260.90' WEST TO A 1/2" REBAR WITH HIS "LS 1127" CAP HE SET FOR THE SOUTHWEST CORNER OF SECTION 18-20-12 ON THE RANGE LINE
  - 4) 2,643.02' SOUTH TO THE 1/2" REBAR OF **UNKNOWN ORIGIN** THAT HE FOUND BUT HE DID **NOT** ACCEPT FOR THE EAST 1/4 CORNER OF SECTION 19-20-12

NORTHWEST CORNER 20-20-12