

WEST 1/4 CORNER SECTION 20, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) ON PAGE 563 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 11" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 20-20-12.

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 152, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 152 DATED NOVEMBER 22 & 23, 1886 ORDERED BY H. F. LAMB TO LOCATE THE LINES AND CORNERS TO THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 20-20-12, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 20-20-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,317.5' EAST TO THE 4" X 9" X 13" LIMESTONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 20-20-12
 - 2) 2,635' EAST TO THE 5" X 8" X 14" LIMESTONE MARKED "C" HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 20-20-12

- 3) MARION WAYNE BLACKBOURN, L.S. 1127, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 13, 1995, FOR PROJECT NUMBER 95-03-050, SURVEY F18001 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR THE SURVEY OF THE SOUTHWEST QUARTER OF SECTION 18-20-12 FOR DON HAGGMAN, RECORDED IN VOLUME 493 ON PAGE 167 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 1, 1995, SAID THAT **HE FOUND A 1/2" REBAR** OF UNKNOWN ORIGIN AT THE EAST 1/4 CORNER OF SECTION 19-20-12. HE DUG AROUND AND PROBED UNDER THE REBAR, BUT **NO STONE** WAS FOUND. HE FOUND NO RECORD OF A SURVEY FOR THIS REBAR, SO **HE DID NOT ACCEPT THIS REBAR** AS THE EAST 1/4 CORNER OF SECTION 19-20-12 AT THIS TIME, AND HE DID NOT TURN IN ANY TIES TO THE REBAR.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,643.02' NORTH TO THE 1/2" REBAR WITH HIS "LS 1127" CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 18-20-12
 - 2) 5,286.04' NORTH TO THE 1/2" REBAR WITH HIS "LS 1127" CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 18-20-12

WEST QUARTER CORNER 20-20-12