

WEST 1/4 CORNER SECTION 25, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) ON PAGE 546 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 14" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 25 & 26-2012.

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 205 DATED MAY 1, 1878 ORDERED BY THOMAS E. WELCH TO SURVEY THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 26-20-12, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 26-20-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/ DRAWING SHOW THE FOLLOWING INFORMATION:
 - 1) 79 RODS, 21-1/2 LINKS NORTH TO THE LOCATION FOR THE EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 26-20-12
 - 2) 159 RODS, 18 LINKS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 26-20-12
 - 3) 79 RODS, 20-1/2 LINKS WEST TO THE LOCATION FOR THE SOUTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 26-20-12
 - 4) 159 RODS, 16 LINKS WEST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 26-20-12

WEST QUARTER CORNER 25-20-12