

CENTER CORNER OF SECTION 26, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 205 DATED MAY 1, 1878 ORDERED BY THOMAS E. WELCH TO SURVEY THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 26-20-12, SAID THAT **HE SET A STONE** FOR THE PERMANENT CENTER CORNER OF SECTION 26-20-12 AT THE INTERSECTION OF THE LINE FROM THE 1/4 CORNER HE FOUND ON THE EAST LINE OF SECTION 26-20-12 TO THE 1/4 CORNER HE FOUND ON THE WEST LINE OF SECTION 26-20-12 WITH THE LINE FROM THE STONE THAT HE FOUND ON THE NORTH LINE OF SECTION 26-20-12 TO THE STONE HE FOUND AT THE 1/4 CORNER ON THE SOUTH LINE OF SECTION 26-20-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/ DRAWING SHOW THE FOLLOWING INFORMATION:
 - 1) 79 RODS, 23-1/2 LINKS NORTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE NE1/4 OF SECTION 26-20-12
 - 2) 159 RODS, 22 LINKS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 26-20-12
 - 3) 79 RODS, 20-1/2 LINKS EAST TO THE LOCATION FOR THE SOUTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 26-20-12
 - 4) 159 RODS, 16 LINKS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 26-20-12

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON PAGE 198 DATED SEPTEMBER 22, 1880, FOR A ROAD SURVEY IN TOWNSHIPS 20-12 & 20-13 APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 26-20-12 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING DISTANCE:
 - 1) THE SECOND ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 26-20-12 TO COMMENCE THE SECOND ROAD ON THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 97 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 390 TO 392 PETITIONED BY WILLIAM SHOCKLEY AND OTHERS FOR THE LOCATION OF TWO COUNTY ROADS IN TOWNSHIPS 20-13 AND 20-13, AND THE VACATION OF A COUNTY OR OLD STATE ROAD IN TOWNSHIP 20-12, THAT HE SURVEYED ON SEPTEMBER 22, 1880, WERE ESTABLISHED AS 50 FEET WIDE ROADS ON JANUARY 6, 1881 AS NOTED BY I. A. TAYLOR, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 6, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 26-20-12 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY. THE ROAD **VACATED** WAS THAT PORTION OF A COUNTY ROAD OR OLD STATE ROAD AS NOW LOCATED THROUGH SECTIONS 14-20-12 & 23-20-12 TO THE CENTER OF SECTION 26-20-12.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THE SECOND ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE FOR 2,640' TO THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 26-20-12 TO COMMENCE THE SECOND ROAD ON THIS ROAD SURVEY

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED MARCH 29, 2011 FOR PROJECT NUMBER 11061-02, SURVEY F26002 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR A SURVEY OF A 6.0 ACRE TRACT IN THE SOUTHWEST QUARTER OF SECTION 26-20-12 FOR BRENDA GORDON, SAID THAT **HE FOUND A 5/8" REBAR WITH A LYON COUNTY CAP** AT THE CENTER

CORNER OF SECTION 26-20-12 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE.

- 1) 7.0' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "T5" NORTH-SOUTH
- 2) 65.0' NORTH TO A 1/2" REBAR WITH "LS 752" CAP
- 3) 35.0' WSW TO A NAIL & WASHER IN A POWER POLE
- 4) 78.60' NNW TO A NAIL & WASHER IN A CORNER FENCE POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,116.37' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE 6.0 ACRE TRACT
- 2) 2,619.37' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A **WITNESS CORNER**
- 3) 2,639.37' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 26-20-12 AND THE NORTHWEST CORNER OF THE 6 ACRE TRACT

CENTER CORNER 26-20-12