

WEST 1/4 CORNER SECTION 27, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) ON PAGE 554 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 24" X 13" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 28-20-12.

- 2) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 61, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 59 DATED JUNE 30, 1870 TO ESTABLISH THE 1/4 CORNER OF SECTION 27-20-12 AND ALSO THE CENTER CORNER OF SAID SECTION 27, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 27-20-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 80.25 CHAINS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 27-20-12

- 3) S. K. McCRARY, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 126, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 207 DATED MAY 9, 1905 AT THE REQUEST OF W. C. LONG AND E. B. VAN NESS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE SOUTHEAST 1/4 OF SECTION 28-20-12 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE EAST 1/4 CORNER OF SECTION 28-20-12 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 2 ON PAGE 148 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 157" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.03 CHAINS NORTH TO THE 3" X 12" X 6" STONE MARKED "H" ON THE WEST SIDE, "II" ON THE SOUTH SIDE, AND "III" ON THE EAST SIDE, THAT HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 28-20-12
 - 2) 40.04 CHAINS SOUTH TO THE STONE MARKED "I" ON THE SOUTH SIDE AND "III" ON THE EAST SIDE WITH "H" ON THE WEST SIDE, THAT HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 28-20-12

WEST QUARTER CORNER 27-20-12