

NORTH 1/4 CORNER SECTION 29, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) ON PAGE 563 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 29-20-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.02 CHAINS WEST TO THE 24" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-20-12
 - 2) 40.01 CHAINS EAST TO THE 24" X 12" X 3" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-20-12

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 44 DATED FEBRUARY 14, 1883 FOR A ROAD IN TOWNSHIP 20, RANGE 12 FOR H. F. LAMB, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 29-20-12 AT A TURN ON THIS ROAD SURVEY. NO WIDTH IS RECORDED ON THIS ROAD SURVEY,
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW/14 OF SECTION 29-20-12 AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE FOR 1-1/2 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 32-20-12 TO COMMENCE THIS ROAD SURVEY

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 209 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 422 TO 424 PETITION BY H. F. LAMB AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 20-12 [PACKET 469 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 14, 1883, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON APRIL 13, 1883, AND WAS RECORDED ON MAY 8, 1883 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 29-20-12 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 3) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW/14 OF SECTION 29-20-12 AT THE TERMINUS OF THIS ROAD SURVEY
 - 4) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE FOR 1-1/2 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 32-20-12 TO COMMENCE THIS ROAD SURVEY

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 271 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 34 TO 36 PETITIONED BY HUGH ROBERTS AND OTHERS FOR THREE ROADS IN TOWNSHIP 20-12 [PACKET 515 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 15, 1884, WAS ESTABLISHED AS A 40 FOOT WIDE NORTH-SOUTH AND 50 FOOT WIDE EAST-WEST ROADS ON JULY 15, 1884, AS NOTED BY P. Y. HALLBERG, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON NOVEMBER 20, 1884 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **FOUND THE STONE** THE WEST 1/4 CORNER OF SECTION 29-20-12 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY. **[NOTE:** HE RAN 1/2 MILE EAST FROM THE NORTHEAST CORNER OF SECTION 30-20-12, MAKING THIS POINT THE NORTH 1/4 CORNER OF SECTION 29-20-12 – WARREN CHIP WOODS, L.S 603, COUNTY SURVEYOR]

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS SECOND ROAD EXTENDS WEST ON THE SECTION LINES FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-20-12 TO BEGIN THE SECOND ROAD ON THIS ROAD SURVEY

- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 152, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 152 DATED NOVEMBER 22 & 23, 1886 ORDERED BY H. F. LAMB TO LOCATE THE LINES AND CORNERS TO THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 20-20-12, SAID THAT **HE FOUND THE OLD STONE** AT THE SOUTH 1/4 CORNER OF SECTION 20-20-12 ON THIS **PERMANENT SURVEY, AND HE SET THE STONE DEEPER IN THE GROUND.**

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,631' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 20-20-12
- 2) 1,317' WEST TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 20-20-12
- 3) 2,634' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 20-20-12
- 4) 5,259' WEST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 19-20-12

- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 10, 2000, FOR PROJECT NUMBER 00070-02, SAID THAT **HE FOUND A 1/2" REBAR** OF UNKNOWN AND UNCERTAIN ORIGIN AT THE NORTH 1/4 CORNER OF SECTION 29-20-12, BUT IN A REASONABLE POSITION FOR THE SECTION CORNER.

- 1) 30.6' SE TO A CONCRETE NAIL & BOTTLE CAP IN A CORNER FENCE POST
- 2) 23.4' NORTH TO A CONCRETE NAIL & BOTTLE CAP IN A CORNER FENCE POST
- 3) IN LINE WITH A FENCE TO THE NORTH
- 4) 3' SOUTH TO THE CENTERLINE TRAVELED WAY EAST-WEST

- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 13, 2010 FOR PROJECT NUMBER 10347-02, A SURVEY WHERE NO DRAWING WAS REQUIRED, SAID THAT **HE FOUND THE 1/2" REBAR** OF UNKNOWN ORIGIN AT THE NORTH 1/4 CORNER OF SECTION 29-20-12 FROM HIS EXISTING REFERENCE TIES ON FILE IN THE COUNTY ENGINEER'S OFFICE IN 2000. [**NOTE:** HE HAD PREVIOUSLY DETERMINED THAT THIS IRON PIN WAS IN A REASONABLE POSITION FOR THE SECTION CORNER – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

- 1) 23.4' NORTH TO A SPIKE & BOTTLE CAP IN A CORNER FENCE POST
- 2) 39.35' NE TO A SPIKE & BOTTLE CAP IN THE TOP OF A FENCE POST
- 3) 31.2' SE TO A SPIKE & BOTTLE CAP IN THE TOP OF A CORNER FENCE POST
- 4) IN LINE WITH A FENCE TO THE NORTH
- 5) 3' SOUTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST

NORTH QUARTER CORNER 29-20-12