

**WEST 1/4 CORNER SECTION 29, TOWNSHIP 20 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 562 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 30-20-12.
  
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 27, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 27 DATED MAY 3, 1884 AT THE REQUEST OF FRED LYMAN TO SURVEY THE WEST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 30-20-12, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 30-20-12 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,641.0' WEST TO THE THEORETICAL LOCATION FOR THE CENTER CORNER OF SECTION 30-20-12
  - 2) 3,961.5' WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8<sup>TH</sup> CORNER OF THE SW 1/4 OF SECTION 30-20-12
  - 3) 5,282.0' WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 30-20-12 ON THE RANGE LINE
  
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN LAND SURVEY REFERENCE REPORT DATED DECEMBER 13, 2010 FOR PROJECT NUMBER 10347-02, A SURVEY WHERE NO DRAWING WAS REQUIRED, SAID THAT HE SEARCHED FOR THE McCRARY STONE RECORDED IN SURVEY BOOK "F" ON PAGE 207 AT THE WEST 1/4 CORNER OF SECTION 29-20-12, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 5/8" X 30" REBAR WITH A LYON COUNTY CAP** FOR THE WEST 1/4 CORNER OF SECTION 29-20-12.
  - 1) 20.9' EAST TO THE TOP CENTER OF A 5" PIPE CORNER FENCE POST
  - 2) 23.7' ESE TO THE TOP CENTER OF A 5" PIPE CORNER FENCE POST
  - 3) IN LINE WITH A FENCE TO THE EAST EXTENDED
  - 4) 1.0' EAST TO A FENCE TO THE NORTH EXTENDED

WEST QUARTER CORNER 29-20-12