

NORTH 1/4 CORNER SECTION 30, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) ON PAGE 563 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 15" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 30-20-12.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING DISTANCES:

- 1) 39.81 CHAINS WEST TO THE 18" X 14" X 4-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-20-12 ON THE WEST TOWNSHIP BOUNDARY
 - 2) 40.00 CHAINS EAST TO THE 24" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-20-12
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 152, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 152 DATED NOVEMBER 22 & 23, 1886 ORDERED BY H. F. LAMB TO LOCATE THE LINES AND CORNERS TO THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 20-20-12, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 19-20-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,625' EAST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 20-20-12
- 2) 3,942' EAST TO THE 5" X 7" X 14" LIMESTONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 20-20-12
- 3) 5,259' EAST TO THE STONE HE FOUND AND **HE SET DEEPER IN THE GROUND AT THE SOUTH 1/4 CORNER OF SECTION 20-20-12**
- 4) 7,890' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 20-20-12

NORTH QUARTER CORNER 30-20-12