

NORTH 1/4 CORNER SECTION 31, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) ON PAGE 562 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 15" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 30 & 31-20-12 ON JULY 11, 1857.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.81 CHAINS WEST TO THE 22" X 15" X 5" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-20-12 ON THE WEST TOWNSHIP BOUNDARY
 - 2) 40.00 CHAINS EAST TO THE 21" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-20-12

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 27, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 27 DATED MAY 3, 1884 AT THE REQUEST OF FRED LYMAN TO SURVEY THE WEST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 30-20-12, SAID THAT **HE SET A STONE** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 30-20-13 ON LINE AND HALF WAY BETWEEN THE STONES THAT HE FOUND AT THE SOUTHEAST AND SOUTHWEST CORNERS OF SECTION 30-20-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,320' WEST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE SW 1/4 OF SECTION 30-20-12
 - 2) 2,640' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 30-20-12 ON THE RANGE LINE
 - 3) 2,640' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 30-20-12

NORTH QUARTER CORNER 31-20-12