

NORTH 1/4 CORNER SECTION 32, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) ON PAGE 561 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 14" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 32-20-12.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.08 CHAINS WEST TO THE 21" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-20-12
- 2) 40.08 CHAINS EAST TO THE 20" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-20-12

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 44 DATED FEBRUARY 14, 1883 FOR A ROAD IN TOWNSHIP 20, RANGE 12 FOR H. F. LAMB, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 32-20-12 ON THIS ROAD SURVEY. NO WIDTH IS RECORDED ON THIS ROAD SURVEY,

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 29-20-12; THEN CONTINUES EAST ON THE SECTION LINES FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 29-20-12 AT THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE FOR 160 RODS TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 32-20-12 TO COMMENCE THIS ROAD SURVEY

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 209 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 422 TO 424 PETITION BY H. F. LAMB AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 20-12 [PACKET 469 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 14, 1883, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON APRIL 13, 1883, AND WAS RECORDED ON MAY 8, 1883 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 32-20-12 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 3) THIS ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 29-20-12; THEN CONTINUES EAST ON THE SECTION LINES FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 29-20-12 AT THE TERMINUS OF THIS ROAD SURVEY
- 4) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE FOR 160 RODS TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 32-20-12 TO COMMENCE THIS ROAD SURVEY

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 10, 2000, FOR PROJECT NUMBER 00070-02, SAID THAT **HE FOUND THE BOTTOM PART OF THE GLO STONE** FIRM IN THE GROUND WITH BROKEN PIECES NEARBY AT THE NORTH 1/4 CORNER OF SECTION 32-20-12. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP THROUGH THE REMAINS OF THE GLO STONE** FOR THE NORTH 1/4 CORNER OF SECTION 32-20-12.

- 1) **8.5' SSE TO A 1/2" REBAR FOUND**
- 2) 26.25' SW TO A 40 D NAIL IN THE TOP OF A TREE STUMP
- 3) 118.6' NNE TO A CONCRETE NAIL & BOTTLECAP IN A POWER POLE

HIS TIES ARE CONTINUED ON PAGE 2

- 4) 2' WEST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 13, 2010 FOR PROJECT NUMBER 10347-02, A SURVEY WHERE NO DRAWING WAS REQUIRED, SAID THAT **HE FOUND THE 5/8" REBAR OVER THE GLO STONE** AT THE SOUTH 1/4 CORNER OF SECTION 29-20-12 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE IN 2000 WHEN HE FOUND THE GLO STONE.
 - 1) **8.55' SSE TO A 1/2" REBAR FOUND**
 - 2) 2' WEST TO THE CENTERLINE TRAVELED WAY OF THE GRAVEL ROAD NORTH-SOUTH
 - 3) 26.25' SW TO A 40 D NAIL IN THE TOP OF A TREE STUMP
 - 4) 118.6' NNE TO A CONCRETE NAIL & BOTTLECAP IN A POWER POLE
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 29, 2014, FOR PROJECT NUMBER 14187-02, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR A SURVEY OF TWO TRACTS IN THE NORTH HALF OF THE SOUTHEAST QUARTER OF SECTION 32-20-12 FOR GOODELL, SAID THAT **HE FOUND THE 5/8" IRON PIN WITH A LYON COUNTY CAP OVER THE GLO STONE** AT THE NORTH 1/4 CORNER OF SECTION 32-20-12 FROM HIS EXISTING REFERENCE TIES DATED DECEMBER 13, 2010 FOR HIS PROJECT NUMBER 10347-02 ON FILE AT THE LYON COUNTY ENGINEERS OFFICE. [**NOTE:** SEE SURVEY F32002 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR A REVISED DESCRIPTION FOR TRACT 1 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
 - 1) **8.55' SSE TO A 1/2" IRON PIN FOUND**
 - 2) 2.00' WEST TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD "P5" NORTH-SOUTH
 - 3) 118.60' NNE TO A CONCRETE NAIL & BOTTLECAP IN A POWER POLE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,638.39' SOUTH TO THE 2-1/2" MAG NAIL WITH WASHER HE SET FLUSH WITH THE ASPHALT ROAD FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 32-20-12, AND THE P.O.B. OF TRACT 1
 - 2) 3,238.89' SOUTH TO THE SOUTHWEST CORNER OF TRACT 1, AS WITNESSED BY THE 1/2" X 24" IRON PIN WITH HIS "S. BROSEMER" CAP HE SET AT 25.00' EAST
 - 3) 3,592.92' SOUTH TO THE 1/2" X 24" IRON PIN WITH HIS "S. BROSEMER" CAP HE SET FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE SE1/4 OF SECTION 32-20-12, AS WITNESSED BY THE 1/2" X 24" IRON PIN WITH HIS "S. BROSEMER" CAP HE SET AT 25.00' EAST
 - 4) 5,267.45' SOUTH TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 32-20-12 ON THE 4TH STANDARD PARALLEL

NORTH QUARTER CORNER 32-20-12