

SOUTH 1/4 CORNER SECTION 33, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) ON PAGE 20 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE ROCK 22" X 10" X 2-1/2"** ON A SLOPE TO THE SOUTHEAST FOR THE SOUTH 1/4 CORNER OF SECTION 33-20-12 ON THE SOUTH TOWNSHIP BOUNDARY AND THE 4TH STANDARD PARALLEL ON NOVEMBER 19, 1855.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE SOUTH TOWNSHIP BOUNDARY AND THE 4TH STANDARD PARALLEL TO THE 22" X 9" X 2-1/2" LIMESTONE THEY SET IN A CREEK BOTTOM FOR THE CORNER TO SECTIONS 32 & 33-20-12
 - 2) 40.00 CHAINS EAST ON THE SOUTH TOWNSHIP BOUNDARY AND THE 4TH STANDARD PARALLEL TO THE 20" X 9" X 3" SANDSTONE THEY SET ON A SLOPE TO THE NORTH FOR THE CORNER TO SECTIONS 33 & 34-20-12
- 2) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER FIFTY-NINE, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 57 DATED JUNE 29, 1870 TO ESTABLISH THE 1/4 CORNER ON THE SOUTH LINE OF SECTION 33-20-12, SAID THAT **HE SET A LIMESTONE** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 33-20-12 ON THE SOUTH TOWNSHIP BOUNDARY AND THE 4TH STANDARD PARALLEL AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-20-12 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-20-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST ON THE 4TH STANDARD PARALLEL TO THE STONE THAT HE FOUND AT THE CORNER OF SECTIONS 33 & 34-20-12
 - 2) 40.00 CHAINS WEST ON THE 4TH STANDARD PARALLEL TO THE STONE THAT HE FOUND AT THE CORNER OF SECTIONS 32 & 33-20-12
- 3) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER SIXTY, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 58 DATED JUNE 29, 1870 TO RUN OUT THE LINES OF 14-3/8 ACRES OF LAND SITUATED IN THE NORTHEAST 1/4 OF SECTION 4-21-12, 50 RODS NORTH & SOUTH AND THE WIDTH OF THE JOG BETWEEN TOWNSHIPS 20 & 21, WHICH IN THIS CASE IS 46 RODS, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 33-20-12 ON THE 4TH STANDARD PARALLEL ON THIS **PERMANENT SURVEY**. THIS SECTION CORNER IS ALSO THE NORTHWEST TRACT CORNER.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 11.50 CHAINS EAST ON THE 4TH STANDARD PARALLEL TO THE STONE HE FOUND AT THE CORNER OF SECTIONS 3 & 44-21-12
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 82 OF THE 7TH TERM, A ROAD SURVEY IN TOWNSHIP 20-12 RECORDED IN SURVEY BOOK "C" ON PAGE 4 DATED JANUARY 27, 1873 FOR J. P. ROSS, ET AL, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 33-20-12 ON THE 4TH STANDARD PARALLEL TO BEGAN THIS ROAD SURVEY.

HIS SURVEY NOTES SHOW THE FOLLOWING ROAD DESCRIPTION:

- 1) COUNTY ROAD PETITIONED BY J. P. ROSS, ET AL. BEGAN AT THE 1/4 CORNER ON THE 4TH STANDARD PARALLEL ON THE SOUTH SIDE OF SECTION 33, TOWNSHIP 20, RANGE 12 AND RAN NORTH ON THE CENTERLINE OF SAID SECTION 33 AND AT 5,280 FEET THE 1/4 CORNER BETWEEN SECTIONS 28 & 33; AT 990 FEET EAGLE CREEK COURSES EAST, AT 2,300 FEET A BRANCH COURSES SE SKIRTED WITH BRUSH, AT 5,280 FEET THE 1/4 CORNER BETWEEN SECTIONS 21 & 28; THENCE WEST ON THE SECTION LINE 2,640 FEET TO THE CORNER TO

SECTIONS 20, 21, 28 & 29 AT THE TERMINUS OF THIS ROAD SURVEY. TOTAL DISTANCE 2-1/2 MILES.

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 207 [PACKET 98 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY J. P. ROSS AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 19-12 THAT HE SURVEYED ON JANUARY 27, 1873, AND WAS ORDERED ESTABLISHED BY THE COUNTY COMMISSIONERS AT A MEETING HELD APRIL 7, 1873 AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 33-20-12 ON THE SOUTH TOWNSHIP BOUNDARY AND THE 4TH STANDARD PARALLEL TO BEGIN THIS ROAD SURVEY.

HIS FIELD NOTES SHOWS THE FOLLOWING ROAD DESCRIPTION:

- 1) BEGINNING AT THE 1/4 CORNER ON THE 4TH STANDARD PARALLEL ON THE SOUTH SIDE OF SECTION 33 TOWNSHIP 20 RANGE 12 AND RUNNING NORTH ON THE NORTH AND SOUTH CENTER LINE OF SAID SECTION 33 AT ONE MILE THE 1/4 CORNER BETWEEN SECTIONS 28 & 33, AT 60 RODS FROM THIS 1/4 CORNER EAGLE CREEK COURSES EAST, 130 RODS A SMALL BRANCH COURSES SOUTHEAST, AT 2 MILES FROM BEGINNING THE 1/4 CORNER BETWEEN SECTIONS 21 & 28; THENCE WEST 1/2 MILE TO THE CORNER OF SECTIONS 20, 21, 28 & 29
 - 2) TOTAL DISTANCE 2-1/2 MILES
 - 3) THE VIEWERS RECOMMENDED THAT SAID ROAD BE GRANTED 40 FEET WIDE AS LOCATED AND SURVEYED
- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 39 OF THE 8TH TERM RECORDED IN SURVEY BOOK "C" ON PAGE 96, A ROAD SURVEY PETITIONED FOR BY J. L. WILLIAMS FOR A COUNTY ROAD IN TOWNSHIP 20, RANGE 12 DATED AUGUST 25, 1874, APPARENTLY **FOUND THE STONE** AT THE 1/4 CORNER ON THE SOUTH BOUNDARY OF SECTION 33-20-12 ON THE 4TH STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY.

THE ROAD IS DESCRIBED AS FOLLOWS:

- 1) BAGAN AT THE 1/4 CORNER BETWEEN SECTIONS 34 & 35, TOWNSHIP 20, RANGE 12, AND RAN SOUTH ON SECTION LINE VARIANCE 11° E. SET ANGLE POST ABOUT 60 FEET FROM LEFT BANK OF EAGLE CREEK A SHORT DISTANCE BELOW THE JUNCTION OF HARPER AND EAGLE CREEK BRANCH, THENCE S. 37°35' W. AT A DISTANCE OF FROM SECTION LINE 132 FEET SET A MULBERRY POST; THENCE S. 1° E. FROM SECTION LINE 185 FEET CROSS SOUTH BRANCH OF EAGLE GREEK COURSES SE FROM SECTION LINE 316-1/2 FEET INTERSECTED 4TH STANDARD PARALLEL 132 FEET WEST OF THE CORNER OF SECTIONS 35 & 34, THENCE WEST ON THE 4TH STANDARD PARALLEL TO THE 1/4 CORNER ON THE SOUTH SIDE BOUNDARY OF SECTION 33.

- 7) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 216 & 217 [PACKET 264 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY J. L. WILLIAMS AND OTHERS FOR A ROAD IN TOWNSHIP 20-12 THAT HE SURVEYED ON AUGUST 25, 1874, AND WAS ESTABLISHED ON OCTOBER 16, 1874 AS ATTESTED BY J. S. CRAIG, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 33-20-12 ON THE 4TH STANDARD PARALLEL TO END THIS ROAD SURVEY.

HIS FIELD NOTES AND PLAT SHOW THE FOLLOWING INFORMATION:

- 1) BEGINNING AT THE 1/4 CORNER BETWEEN SECTIONS 34 & 35 AND RUNNING SOUTH ON THE SECTION LINE 144.13 RODS; THENCE S. 37°35' W. 8 RODS; THENCE S. 1° E. CROSSING SOUTH BRANCH OF EAGLE CREEK 10.57 RODS INTERSECTING THE 4TH STANDARD PARALLEL SOUTH AT 8 RODS WEST OF THE

CORNER BETWEEN SECTIONS 34 AND 35, TOWNSHIP 20, RANGE 12 ; THENCE WEST ON SAID 4TH STANDARD PARALLEL ABOUT 1-1/2 MILES TO THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 33 TOWNSHIP 20 RANGE 12

- 2) TOTAL DISTANCE 1-1/2 MILES AND 154.7 RODS
- 3) VIEWERS RECOMMENDED THAT SAID ROAD BE OPENED FORTY FEET WIDE AS LOCATED AND SURVEYED

- 8) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 130 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 106 TO 108 PETITIONED BY J. P. ROSS AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 21-12 THAT HE SURVEYED ON SEPTEMBER 30, 1881, WAS ESTABLISHED ON OCTOBER 5, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 14, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 33-20-12 ON THE SOUTH TOWNSHIP BOUNDARY AND THE 4TH STANDARD PARALLEL TO COMMENCE THIS ROAD SURVEY.

HIS FIELD NOTES AND PLAT SHOWS THE FOLLOWING INFORMATION:

- 1) COMMENCING AT THE 1/4 CORNER ON THE SOUTH SIDE OF SECTION 33-20-12; THENCE S. 10°45' E. 350 FEET; THENCE WEST VARIANCE 10°45' 40 FEET; THENCE S. 10°45' 2,660' TO THE 1/2 SECTION LINE; THENCE EAST VARIANCE 10°45' 800 FEET TO THE 1/4 SECTION CORNER ON THE EAST SIDE OF SECTION 4-21-12; THENCE S. 10°45' E. 2,640 FEET TO THE SOUTHEAST CORNER OF SECTION 4-21-12; THENCE S. 10°45' E. 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 9-21-12; THENCE S. 10°45' E. 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 16-21-12; THENCE S. 10°45' E. 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 21-21-12; THENCE S. 10°45' E. 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 28-21-12; THENCE S. 10°45' E. 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 33-21-12 AT THE TERMINUS OF THIS ROAD SURVEY ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE
- 2) THE VIEWERS WERE OF THE OPINION THAT SAID ROAD IS PRACTICABLE AND OF PUBLIC UTILITY, AND RECOMMENDED THAT IT BE GRANTED AS LOCATED AND SURVEYED, AND THAT IT BE ESTABLISHED AND OPENED FORTY FEET WIDE TO THE SECTION LINE AND 50 FEET WIDE FROM THE SECTION LINE SOUTH

- 9) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 225 DATED SEPTEMBER 30, 1881, FOR A ROAD SURVEY IN TOWNSHIP 21-12 SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 33-20-12 ON THE SOUTH TOWNSHIP BOUNDARY AND THE 4TH STANDARD PARALLEL TO COMMENCE THIS ROAD SURVEY

HIS FIELD NOTES AND PLAT SHOWS THE FOLLOWING INFORMATION:

- 1) COMMENCING AT THE 1/4 CORNER ON THE SOUTH SIDE OF SECTION 33-20-12; THENCE S. 10°45' E. 350 FEET; THENCE WEST VARIANCE 10°45' 40 FEET; THENCE S. 10°45' 2,660' TO THE 1/2 SECTION LINE; THENCE EAST VARIANCE 10°45' 800 FEET TO THE 1/4 SECTION CORNER ON THE EAST SIDE OF SECTION 4-21-12; THENCE S. 10°45' E. 2,640 FEET TO THE SOUTHEAST CORNER OF SECTION 4-21-12; THENCE S. 10°45' E. 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 9-21-12; THENCE S. 10°45' E. 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 16-21-12; THENCE S. 10°45' E. 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 21-21-12; THENCE S. 10°45' E. 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 28-21-12; THENCE S. 10°45' E. 5,280 FEET TO THE SOUTHEAST CORNER OF SECTION 33-21-12 AT THE TERMINUS OF THIS ROAD SURVEY ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE

CONTINUED ON PAGE 4

- 10) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 27, 1983, SURVEY F04001 IN THE SURVEY FILE FOR TOWNSHIP 21-12, SAID THAT **HE FOUND A 1/2" REBAR AT 16" DEEP OF UNCERTAIN ORIGIN** BUT IN A "**REASONABLE**" POSITION FOR THE SOUTH 1/4 CORNER OF SECTION 33-20-12 ON THE SOUTH TOWNSHIP BOUNDARY AND THE 4TH STANDARD PARALLEL. HE SAID THAT THIS REBAR WAS USED BY GREGORY A. MILES, L.S. 667, IN A SURVEY RECORDED IN BOOK 365 ON PAGE 239 IN THE REGISTER OF DEEDS OFFICE. HE HAD EXCAVATED FOR THE STONE AT THIS CORNER WITH A COUNTY MAINTAINER, BUT HE DID **NOT** FIND THE STONE. **HE SET A 5/8" X 24" CAPPED REBAR OVER THE 1/2" REBAR THAT HE FOUND** FOR THE SOUTH 1/4 CORNER OF SECTION 33-20-12 ON THE SOUTH TOWNSHIP BOUNDARY AND THE 4TH STANDARD PARALLEL.
- 1) 756.0' EAST TO THE NORTHEAST CORNER OF SECTION 4-21-12 ON THE 4TH STANDARD PARALLEL
 - 2) 38.5' SE TO A SPIKE & WASHER IN THE TOP OF A GATE POST
 - 3) 30.5' NE TO A SPIKE & WASHER IN THE TOP OF A LONE POST
 - 4) 3.0' NORTH TO THE TRAVELED WAY OF THE ROAD TO THE EAST
 - 5) 1.0' WEST TO THE TRAVELED WAY OF THE ROAD TO THE NORTH
- 11) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 8, 2003, FOR BRIDGE REPLACEMENT PROJECT NUMBER 03-CM, **FOUND THE 5/8" REBAR WITH A BROKEN CAP AT 6" BELOW THE ROAD SURFACE** AT THE SOUTH 1/4 CORNER OF SECTION 33-20-12 ON THE SOUTH TOWNSHIP BOUNDARY AND THE 4TH STANDARD PARALLEL FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S. 752, DATED APRIL 1983, THAT NOTED THAT THIS 5/8" REBAR IS OVER A 1/2" REBAR HE FOUND AT 16" DEEP. **I PLACED A NEW LYON COUNTY CAP ON THE REBAR** AT THE SOUTH 1/4 CORNER OF SECTION 33-20-12 ON THE 4TH STANDARD PARALLEL.
- 1) 36.1' SE TO A SPIKE & WASHER IN THE TOP OF THE NORTH GATE POST
 - 2) 40.8' SSE TO A PK NAIL & WASHER IN THE TOP THE SOUTH GATE POST
 - 3) 42.7' SE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 4) 756.09' EAST TO THE NORTHWEST CORNER OF SECTION 3-21-12 ON THE 4TH STANDARD PARALLEL
- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 29, 2014, FOR PROJECT NUMBER 14187-02, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR A SURVEY OF TWO TRACTS IN THE NORTH HALF OF THE SOUTHEAST QUARTER OF SECTION 32-20-12 FOR GOODELL, SAID THAT **HE FOUND THE 5/8" IRON PIN OVER THE 1/2" IRON PIN** AT THE SOUTH 1/4 CORNER OF SECTION 33-30-12 ON THE SOUTH TOWNSHIP BOUNDARY AND THE 4TH STANDARD PARALLEL FROM EXISTING REFERENCE TIES BY WARREN CHIP WOODS, L.S. 603, DATED JULY 8, 2003 ON FILE AT THE LYON COUNTY ENGINEERS OFFICE. **[NOTE: SEE SURVEY F32002 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR A REVISED DESCRIPTION FOR TRACT 1. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**
- 1) 34.00' NE TO A 16 D NAIL IN THE SOUTHEAST FACE OF A LONE CORNER FENCE POST
 - 2) 36.20' SW TO A 40 D SPIKE IN THE TOP OF A GATE POST
 - 3) 42.85' SSE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 4) IN THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 70 TO THE EAST
 - 5) 6.00' WEST TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD "R5" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
HIS INFORMATION IS CONTINUED ON PAGE 5

- 1) 2,648.64' WEST ON THE 4TH STANDARD PARALLEL TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 32-20-12
 - 2) 5,294.10' WEST ON THE 4TH STANDARD PARALLEL TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 32-20-12
 - 3) 13,230.47' WEST ON THE 4TH STANDARD PARALLEL TO THE 5/8" IRON PIN OVER THE GLO STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-20-12
- 13) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 2, 2016, FOR PROJECT NUMBER 15127-02, SURVEY F33001 IN THE SURVEY FILE FOR TOWNSHIP 20-12 AND SURVEY F03002 IN THE SURVEY FILE FOR TOWNSHIP 21-12, A SURVEY OF THE 4TH STANDARD PARALLEL SOUTH [EXCLUDING THE CLOSING CORNERS] BETWEEN THE SOUTH 1/4 CORNER OF SECTION 33 AND THE SOUTHEAST CORNER OF SECTION 35 IN TOWNSHIP 20 SOUTH, RANGE 12 EAST FOR THE LYON COUNTY ROAD AND BRIDGE DEPARTMENT, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" REBAR WITH A LYON COUNTY CAP** AT THE SOUTH 1/4 CORNER OF SECTION 33-20-12 ON THE 4TH STANDARD PARALLEL FROM HIS EXISTING REFERENCE TIES IN 2014 FOR PROJECT NUMBER 14187.
- 1) TRUE STATE PLANE COORDINATES: KANSAS SOUTH ZONE BY 2 HOUR STATIC GPS OCCUPATION PROCESSED BY OPUS: Y = 1901414.019 X = 2004703.937
 - 2) 36.4' NE TO THE TOP CENTER OF THE SOUTH PIPE BRACE POST
 - 3) 37.3' NE TO THE TOP CENTER OF THE NORTH PIPE BRACE POST
 - 4) 40.9' SE TO A PK ANIL & WASHER IN THE TOP OF A CORNER FENCE POST
 - 5) 5.5' WEST TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD R5 NORTH-SOUTH
 - 6) 1' NORTH TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD 70 TO THE EAST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 756.04' EAST ON THE 4TH STANDARD PARALLEL TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 3-21-12
 - 2) 2,650.96' EAST ON THE 4TH STANDARD PARALLEL TO THE RAILROAD SPIKE HE SET IN A TREE ROOT FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 34-20-12
 - 3) 5,289.53' EAST ON THE 4TH STANDARD PARALLEL TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET WITH A PIECE OF THE GLO STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 34-20-12
 - 4) 7,928.17' EAST ON THE 4TH STANDARD PARALLEL TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET OVER THE 3" X 8" SANDSTONE HE FOUND AT 32" DEEP AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 34-20-12
 - 5) 10,570.19' EAST ON THE 4TH STANDARD PARALLEL TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 35-20-12
 - 6) 13,212.21' EAST ON THE 4TH STANDARD PARALLEL TO THE STONE HE FOUND WITH A 5/8" IRON PIN WITH A LYON COUNTY CAP HE SET ON THE SOUTH SIDE OF THE STONE AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 35-20-12

SOUTH QUARTER CORNER 33-20-12