

SOUTHWEST CORNER SECTION 33, TOWNSHIP 20 SOUTH, RANGE 12 EAST

- 1) ON PAGE 19 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 9" X 2-1/2"** IN THE CREEK BOTTOM FOR THE CORNER TO SECTIONS 32 & 33-20-12 ON THE 4TH STANDARD PARALLEL ON NOVEMBER 18, 1855.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS EAST ON THE 4TH STANDARD PARALLEL TO THE 22" X 10" X 2-1/2" SANDSTONE THEY SET ON A SLOPE TO THE SOUTHEAST FOR THE 1/4 CORNER ON THE SOUTH SIDE OF SECTION 33-20-12
 - 2) 80.00 CHAINS EAST ON THE 4TH STANDARD PARALLEL TO THE 20" X 9" X 3" LIMESTONE THEY SET ON A SLOPE TO THE NORTH FOR THE CORNER TO SECTIONS 33 & 34-20-12

- 2) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 59, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 57 DATED JUNE 29, 1870 TO ESTABLISH THE 1/4 CORNER ON THE SOUTH LINE OF SECTION 33-20-12 ON THE 4TH STANDARD PARALLEL, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 33-20-12 ON THE 4TH STANDARD PARALLEL ON **THIS PERMANENT SURVEY.**
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS EAST ON THE 4TH STANDARD PARALLEL TO THE LIMESTONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 33-20-12
 - 2) 80.00 CHAINS EAST ON THE 4TH STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-20-12

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A PERMANENT SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 198 AND DATED MAY & JUNE 1872, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 33-20-12 ON THE 4TH STANDARD PARALLEL ON **THIS PERMANENT SURVEY.**

- 4) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 7 DATED MAY 27 & 31, 1882, FOR A ROAD IN TOWNSHIP 20-12, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 33-20-12 ON THE 4TH STANDARD PARALLEL. HE USED THIS STONE AND THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-20-12 TO SET A STONE FOR THE WEST 1/4 CORNER OF SECTION 33-20-12 TO BEGIN THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.75 CHAINS NORTH TO THE STONE HE SET FOR THE WEST 1/4 CORNER OF SECTION 33-20-12 TO BEGIN THIS ROAD SURVEY
 - 2) 79.50 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-20-12
 - 3) 159.20 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 28-20-12
 - 4) 238.98 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 21-20-12
 - 5) 318.98 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 16-20-12
 - 6) 399.16 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-20-12
 - 7) 479.26 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 4-20-12 ON THE TOWNSHIP LINE TO END THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 8) S. K. McCrary, Deputy County Surveyor, in Survey Number 126, a **PERMANENT SURVEY** recorded in Survey Book "F" on page 207 dated May 9, 1905 at the request of W. C. Long and E. B. Van Ness for the purpose of locating and permanently establishing the corners and boundaries of the southeast 1/4 of section 28-20-12 and run such lines as may be necessary to properly complete the work, said that **he found the stone about 5 feet west of a north & south hedge** at the southwest corner of section 33-20-12 on the 4th standard parallel on this **PERMANENT SURVEY**. His field notes are in book 2 on page 148 in the "Kretsinger Collection" of field books, and there is additional information in packet "M 157" in miscellaneous drawer number 8 in the vault in the county engineer's office.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 39.78 chains north to the stone he found in place at the west 1/4 corner of section 33-20-12
 - 2) 59.70 chains north to the stone he set for the permanent west 1/8th corner of the NW1/4 of section 22-20-12
 - 3) 79.62 chains north to the stone marked "H 1/4" he set for the permanent southwest corner of section 28-20-12 at 4 feet south of an east & west hedge
 - 4) 99.54 chains north to the stone he set for the permanent west 1/8th corner of the SW1/4 of section 28-20-12 [he noted that Milliken's stone was **NOT** accepted]
 - 5) 119.45 chains north to the stone he set for the permanent west 1/4 corner of section 28-20-12
 - 6) 139.36-1/2 chains north to the stone he set for the permanent west 1/8th corner of the NW1/4 of section 28-20-12
 - 7) 159.28 chains north to the stone he found in place at the northwest corner of section 28-20-12
- 6) STEVEN S. BROSEMER, L.S. 752, County Surveyor, in Survey F04001 in the survey file for township 21-12 for a survey for the Lyon County Highway Department dated April 27, 1983, said that he determined that the position for the southwest corner of section 33-20-12 on the 4th standard parallel falls in a drainage ditch and was **LOST**. He did **NOT** reset the southwest corner of section 33-20-12 on the 4th standard parallel on this survey.
- 7) STEVEN S. BROSEMER, L.S. 752, Deputy County Surveyor, in a land survey reference report dated August 29, 2014, for project number 14187-02, survey F32001 in the survey file for township 20-12 for a survey of two tracts in the north half of the southeast quarter of section 32-20-12 for Goodell, said that he considered that the southeast corner of section 32-20-12 was **LOST**. He reset this corner from the locations he developed between the southwest corner of section 31-20-12 and the south 1/4 corner of section 33-20-12 on the 4th standard parallel as the Lyon County Surveyor for the Lyon County Highway Department dated April 27, 1983. **HE SET A 5/8" IRON PIN WITH A LYON COUNTY CAP** for the southeast corner of section 32-20-12 on the 4th standard parallel. **[NOTE: SEE SURVEY F32002 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR A REVISED DESCRIPTION FOR TRACT 1 - WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**
- 1) THE CORNER FALLS IN THE BOTTOM OF A DRAINAGE CHANNEL TO THE NORTH
 - 2) 11.30' SW TO A CONCRETE NAIL & BOTTLECAP IN A 20" HACKBERRY TREE
- HIS TIES ARE CONTINUED ON PAGE 3

- 3) 12.00' EAST TO A CONCRETE NAIL & BOTTLECAP IN AN 8" HACKBERRY TREE
- 4) IN LINE WITH A FENCE AND TREE ROW TO THE WEST EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,648.64' EAST ON THE 4TH STANDARD PARALLEL TO THE 5/8" IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 33-20-12
- 2) 2,645.46' WEST ON THE 4TH STANDARD PARALLEL TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 32-20-12
- 3) 10,581.83' WEST ON THE 4TH STANDARD PARALLEL TO THE 5/8" IRON PIN HE FOUND OVER THE GLO STONE AT THE SOUTHWEST CORNER OF SEC. 31-20-12
- 4) 1,314.86' NORTH TO THE 1/2" X 24" IRON PIN WITH HIS "S. BROSEMER" CAP HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE SE1/4 OF SEC. 32-20-12
- 5) 2,629.72' NORTH TO THE 2-1/2" MAG NAIL WITH WASHER HE SET FLUSH WITH THE ASPHALT ROAD FOR THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 32-20-12

SOUTHWEST CORNER 33-20-12