

**WEST 1/16<sup>TH</sup> CORNER SOUTHWEST QUARTER OF SECTION 33, TOWNSHIP 20 SOUTH,  
RANGE 12 EAST**

- 1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 29, 2014, FOR PROJECT NUMBER 14187-02, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR A SURVEY OF TWO TRACTS IN THE NORTH HALF OF THE SOUTHEAST QUARTER OF SECTION 32-20-12 FOR GOODELL, SAID THAT **HE SET A 1/2" X 24" IRON PIN WITH HIS "S. BROSEMER" CAP** FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE SOUTHEAST 1/4 OF SECTION 32-20-12 ON TRUE LINE AND HALFWAY BETWEEN THE EAST 1/4 CORNER OF SECTION 32-20-12 AND THE SOUTHEAST CORNER OF SECTION 32-20-12 ON THE 4<sup>TH</sup> STANDARD PARALLEL. [**NOTE:** SEE SURVEY F32002 IN THE SURVEY FILE FOR TOWNSHIP 20-12 FOR A REVISED DESCRIPTION FOR TRACT 1 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

- 1) 7.30' ESE TO A CONCRETE NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
- 2) 1.50' SOUTH TO A LINE OF FENCE EAST-WEST
- 3) 5.50' EAST TO A LINE OF FENCE TO THE NORTH
- 4) 8.00' SW TO A CONCRETE NAIL & WASHER IN A BRACE POST

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,314.86' SOUTH TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 32-20-12 ON THE 4<sup>TH</sup> STANDARD PARALLEL
- 2) 1,314.86' NORTH TO THE 2-1/2" MAG NAIL WITH WASHER HE SET FLUSH WITH THE ASPHALT ROAD AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 32-20-12
- 3) 2,619.84' WEST TO THE 1/2" X 24" IRON PIN WITH HIS "S. BROSEMER" CAP HE SET FOR A **WITNESS CORNER**
- 4) 2,644.84' WEST TO THE 1/2" X 24" IRON PI WITH HIS "S. BROSEMER" CAP HE SET FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE SE1/4 OF SECTION 32-20-12

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 33-20-12