

CENTER CORNER OF SECTION 03, TOWNSHIP 20 SOUTH, RANGE 13 EAST

- 1) LLOYD J. DOBLER, L.S. 541, OF PROFESSIONAL ENGINEERING CONSULTANTS, FOR CONTRACT DACW56-70-C-0158, FOR THE "PARTIAL BOUNDARY SURVEYS "AREA A" JOHN REDMOND RESERVOIR" SURVEYED NOVEMBER 1970 AND FIELD NOTES RECORDED IN SURVEY BOOK NUMBER 5-1790, SURVEY F03001 IN THE SURVEY FILE FOR TOWNSHIP 19-13, SHOWS ON HIS SURVEY DRAWING THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE CENTER CORNER OF SECTION 3-20-13 TO BE AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE QUARTER CORNERS.

NOTE: HE DID **NOT** FIND THE STONES AT THE NORTHEAST OR SOUTHEAST CORNERS OF SECTION 3-20-13, SO HIS DISTANCES BELOW MAY NOT BE CORRECT DUE TO THE WAY THAT HE SET THE NORTH 1/4 CORNER OF SECTION 3-20-12 ON THE 4TH STANDARD PARALLEL – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,664.46' WEST TO THE "ORIGINAL STONE" HE FOUND AT THE WEST 1/4 CORNER OF SECTION 3-20-13
- 2) 2,634.76' NORTH TO THE IRON PIN HE SET FOR THE NORTH 1/4 CORNER OF SECTION 3-20-13 ON THE 4TH STANDARD PARALLEL [SEE **NOTE** ABOVE]
- 3) 2,647.26' EAST TO THE IRON PIN AT THE EAST 1/4 CORNER OF SECTION 3-20-13 ON THE LYON AND COFFEY COUNTY LINE
- 4) 2,621.98' SOUTH TO THE IRON PIN HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 3-20-13

CENTER CORNER 03-20-13