

CENTER CORNER OF SECTION 05, TOWNSHIP 20 SOUTH, RANGE 13 EAST

- 1) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 176, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 176 DATED MAY 24 & 25, 1887 FOR BY J. W. OSBORNE, PRINCIPAL PETITIONER, FOR A COUNTY ROAD IN TOWNSHIP 20-13, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 5-10-13 AT A TURN ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE 1/4 SECTION LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 5-20-13 TO END THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE 1/4 SECTION LINE FOR 20 FEET TO THE ROAD STONE HE SET ON THE EAST SIDE OF A HEDGE, THEN EXTENDS SOUTH PARALLEL TO THE HEDGE TO THE ROAD STONE HE SET AT 20 FEET EAST OF THE SOUTH 1/4 CORNER OF SECTION 5-20-13 TO BEGIN THIS ROAD SURVEY

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 349 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 346 TO 348 PETITIONED BY J. W. OSBORN AND OTHERS FOR A ROAD IN SECTION 5-20-13 [PACKET 602 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 25, 1887, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD AS NOTED BY T. E. McMILLAN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON SEPTEMBER 17, 1887 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 5-20-13 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE 1/4 SECTION LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 5-20-13 TO END THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE 1/4 SECTION LINE FOR 20 FEET TO THE ROAD STONE HE SET ON THE EAST SIDE OF A HEDGE, THEN EXTENDS SOUTH PARALLEL TO THE HEDGE TO THE ROAD STONE HE SET AT 20 FEET EAST OF THE SOUTH 1/4 CORNER OF SECTION 5-20-13 TO BEGIN THIS ROAD SURVEY

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 173, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 173 DATED JUNE 20-24, 1887 ORDERED BY T. GASCHE TO SURVEY THE SOUTHWEST 1/4 OF SECTION 5-20-13, SAID THAT **HE SET A 4" X 9" X 15" LIMESTONE MARKED WITH A "C"** FOR THE PERMANENT CENTER CORNER OF SECTION 5-20-13 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,325-1/2' SOUTH TO THE 5" X 12" X 21" LIMESTONE HE SET FOR THE PERMANENT EAST 1/4/4 CORNER OF THE SW1/4 OF SECTION 5-20-13
 - 2) 2,651' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 5-20-13

- 4) JOHN R. YOUNG, L.S. 112, OF SCHWAB-EATON, P.A., IN A SECTION CORNER REPORT FOR THE PARTIAL BOUNDARY SURVEYS FOR THE JOHN REDMOND DAM AND RESERVOIR UNDER CONTRACT NUMBER DACW56-75-C-0129 RECORDED IN FIELD BOOK NUMBER 5-119 DATED APRIL 1976 AND FILED IN THE REGISTER OF DEEDS OFFICE ON JUNE 29, 1976 IN VOLUME 347 ON PAGE 253-A, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 20-13, SHOWS ON HIS SURVEY DRAWING THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE CENTER CORNER OF SECTION 5-20-13 TO BE AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE QUARTER CORNERS, BUT THE POSITION WAS **NOT** MONUMENTED ON THIS SURVEY. **[NOTE:**

THE POSITION OF THE NORTH 1/4 CORNER OF SECTION 5-20-13 IS **INCORRECT** AS HE DID **NOT** FIND/USE THE BUGGY AXLE FROM THE 1954 PERMANENT SURVEY, WHICH MEANS THAT THE POSITION FOR THIS CENTER CORNER IS ALSO **QUESTIONABLE**. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR] HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,634.21' WEST TO THE CORPS OF ENGINEERS MONUMENT HE SET FOR THE WEST 1/4 CORNER OF SECTION 5-20-13
- 2) 2,665.18' NORTH TO THE 1" IRON BAR HE SET FOR THE NORTH 1/4 CORNER OF SECTION 5-20-13
- 3) 2,634.21' EAST TO THE THEORETICAL LOCATION FOR THE EAST 1/4 CORNER OF SECTION 5 -20-13 AS THE TRUE POSITION FALLS IN THE NEOSHO RIVER
- 4) 2,651.29' SOUTH TO THE 1" IRON BAR HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 5-20-13

CENTER CORNER 05-20-13