

**NORTH 1/4 CORNER SECTION 09, TOWNSHIP 20 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 677 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 9-20-13.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.03 CHAINS WEST TO THE 18" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-20-13
- 2) 40.03 CHAINS EAST TO THE 20" X 10" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-20-13

- 2) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 51, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 50 DATED JUNE 8, 1870 TO ESTABLISH THE CORNER OF SECTIONS 9, 8, 5 & 4, THE CENTER OF SECTION 9, AND THE CENTER OF THE NORTHEAST 1/4 OF SECTION 9, ALL IN TOWNSHIP 20 OF RANGE 13, SAID THAT **HE SET A LIMESTONE** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 9-20-13 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET BY **MUTUAL CONSENT** FOR THE NORTHWEST CORNER OF SECTIONS 9-20-13 AND THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTIONS 9-20-13 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 19.86-1/2 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/2 1/4 CORNER OF THE NE1/4 OF SECTION 9-20-13
- 2) 39.73 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTIONS 9-20-13
- 3) 39.73 CHAINS WEST TO THE STONE HE SET BY **MUTUAL CONSENT** FOR THE PERMANENT NORTHWEST CORNER OF SECTION 9-20-13
- 4) 79.33 CHAINS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 8-20-13
- 5) 79.60 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 8-20-13
- 6) 80.14 CHAINS SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 9-20-13

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 86 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 346 TO 348 PETITION BY WILLIAM BROWN AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 20-13 [PACKET 218 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS SURVEYED ON SEPTEMBER 29, 1880, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 5, 1880 AS NOTED B I. A. TAYLOR, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON NOVEMBER 15, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 9-20-13 TO COMMENCE THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE FOR 5,280 FEET TO THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 9-20-13 AT THE TERMINUS OF THIS ROAD SURVEY

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT SIDE PAGE 186 DATED SEPTEMBER 19, 1880, FOR A COUNTY ROAD IN TOWNSHIP 20-13, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 9-20-13 TO COMMENCE THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) THIS ROAD EXTENDS SOUTH ONE MILE ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 9-20-13 AT THE TERMINUS OF THIS ROAD SURVEY

NORTH QUARTER CORNER 09-20-13