

NORTH 1/4 CORNER SECTION 10, TOWNSHIP 20 SOUTH, RANGE 13 EAST

- 1) ON PAGE 673 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 3-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 10-20-13.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.03-1/2 CHAINS WEST TO THE 20" X 10" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-20-13
 - 2) 40.03-1/2 CHAINS EAST TO THE 20" X 10" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-20-13 ON THE COUNTY LINE
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 5 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 152 DATED JANUARY 23, 1872 TO ESTABLISH THE CENTER OF SECTION 10-20-12, DIVIDE THE SOUTHWEST 1/4 EQUALLY BY A LINE RUNNING NORTH & SOUTH, AND TO SUBDIVIDE THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SAID SECTION 10, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 10-20-13 ON THIS **PERMANENT SURVEY**.
- 3) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS SQUARE HEADED BOLT WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGES 54 AND 55 SAYS THAT **THEY DROVE A SQUARE HEADED BOLT** FOR THE SOUTH 1/4 CORNER OF SECTION 3-20-13 AT 2,663.5' EAST OF THE SOUTHWEST CORNER OF SECTION 3-20-10.
 - 1) 40' SW TO THE IRON HEADWALL OF A CULVERT
 - 2) 16' SOUTH TO THE NORTH END OF A CONCRETE HEADWALL OF A CULVERT
 - 3) 20' NORTH TO A TELEPHONE POLE LINE
- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 20-13 SHOWS A **REA PIN** AT THE "S1/4 CORNER SECTION 3-20-13" AND "N1/4 CORNER SECTION 10-20-13". **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY - WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 20' NORTH TO A WITNESS [REA]
- 5) LLOYD J. DOBLER, L.S. 541, OF PROFESSIONAL ENGINEERING CONSULTANTS, FOR CONTRACT DACW56-70-C-0158, FOR THE "PARTIAL BOUNDARY SURVEYS "AREA A" JOHN REDMOND RESERVOIR" SURVEYED NOVEMBER 1970 AND FIELD NOTES RECORDED IN SURVEY BOOK NUMBER 5-1790, SURVEY F03001 IN THE SURVEY FILE FOR TOWNSHIP 19-13, SHOWS ON HIS SURVEY DRAWING THAT **HE SET AN IRON PIN** FOR THE SOUTH 1/4 CORNER OF SECTION 3-20-13. HE DID NOT DESCRIBE THE IRON PIN OR THE METHODOLOGY THAT HE USED TO DETERMINE THE LOCATION FOR THE CORNER, AND HE DID NOT TURN IN ANY TIES TO THE COUNTY ENGINEER'S OFFICE. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THE SURVEYS FOR JOHN REDMOND WERE POORLY RESEARCHED AND LITTLE, IF ANY, EFFORT WAS MADE TO CHECK FOR THE STONES OF RECORD– WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
NOTE: HE DID **NOT** FIND THE STONE AT THE SOUTHEAST CORNER OF SECTION 3-20-10, SO HIS DISTANCES BELOW TO THE "IRON PINS" THAT HE FOUND AT THE SOUTHEAST AND SOUTHWEST CORNERS ARE **NOT** CORRECT – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) ~~2,666.36' WEST TO THE IRON PIN HE FOUND AT THE SOUTHWEST CORNER OF SECTION 3-20-10~~

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) ~~2,662.55' EAST TO THE IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-20-10~~
- 3) ~~2,631.98' NORTH TO THE CALCULATED POSITION FOR THE CENTER CORNER OF SECTION 3-20-10~~
- 4) ~~5,256.74' NORTH TO THE IRON PIN HE SET FOR THE NORTH 1/4 CORNER OF SECTION 3-20-10~~

NORTH QUARTER CORNER 10-20-13