

**NORTHWEST CORNER SECTION 10, TOWNSHIP 20 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 672 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 3"** FOR THE CORNER TO SECTIONS 3 & 4-20-13.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH TO THE 20" X 10" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTION 3 & 4-20-13
  - 2) 80.30 CHAINS NORTH TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3 & 4-20-13 ON THE TOWNSHIP LINE
  - 3) 40.03-1/2 CHAINS EAST TO THE 16" X 12" X 3-1/2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 10-20-13
  - 4) 80.07 CHAINS EAST TO THE 20" X 10" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-20-13 ON THE COUNTY LINE
- 2) E. B. KIRKENDALL, COUNTY SURVEYOR FROM 1863 TO 1865, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "A" ON PAGE 40 [PACKET 160 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY S. VANGUNDY AND OTHER FOR THE "NEOSHO RAPIDS TO HARTFORD ROAD" THAT WAS SURVEYED JULY 15 & 16, 1863, AND ESTABLISHED IN THE COMMISSIONERS JOURNAL ON PAGE 49, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 10-20-13 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINE TO THE NORTHWEST CORNER OF SECTION 3-20-13 ON THE TOWNSHIP LINE AT A TURN TO THE WEST
  - 2) THIS ROAD EXTENDS SOUTHEASTERLY
- 3) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 51, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 50 DATED JUNE 8, 1870 TO ESTABLISH THE NORTHWEST CORNER OF SECTION 9, THE CENTER CORNER OF SECTION 9, AND THE CENTER CORNER OF THE NORTHEAST 1/4 OF SECTION 9, ALL IN TOWNSHIP 20 OF RANGE 13, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 9-20-13 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 19.86-1/2 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 9-20-13
  - 2) 39.73 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 9-20-13
  - 3) 79.46 CHAINS WEST TO THE STONE HE SET BY MUTUAL CONSENT FOR THE PERMANENT NORTHWEST CORNER OF SECTION 9-20-13
  - 4) 119.06 CHAINS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER ON THE NORTH LINE OF SECTION 8-20-13
  - 5) 159.06 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 8-20-13
- 4) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 52, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 51 DATED JUNE 13, 1870 TO ESTABLISH THE 1/4 SECTION CORNER STONE ON THE NORTH LINE OF SECTION 4-20-13 AND TO ESTABLISH THE CENTER CORNER OF THE SOUTHEAST 1/4 OF SECTION 4-20-13 AND DIVIDE THE SOUTHEAST CORNER OF SECTION 4-20-13 BY A LINE RUNNING EAST & WEST, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 4-20-13 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 19.93 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE SE1/4 OF SECTION 4-20-13

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 39.86 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 4-20-13
  - 3) 59.86 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 4-20-13
  - 4) 80.14 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 4-20-13 ON THE TOWNSHIP LINE
- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 135, A ROAD SURVEY RECORDED IN SURVEY BOOK “B” ON PAGE 134 DATED JULY 25, 1871 FOR A ROAD IN SECTION 10-20-13, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 10-20-13 TO BEGIN THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) 1,140 FEET SOUTH TO AN ANGLE STONE HE SET
- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 176 & 177 [PACKET 24 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY S. E. G. HOLT AND OTHERS FOR A ROAD IN TOWNSHIP 20-13 THAT HE SURVEYED JULY 27, 1871, WAS ORDERED AND ESTABLISHED BY THE BOARD OF COUNTY COMMISSIONERS AS A 50 FOOT WIDE ROAD ON SEPTEMBER 4, 1871, AND WAS FILED FOR RECORD ON SEPTEMBER 4, 1871 BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT HE BEGAN THIS ROAD SURVEY AT THE NORTHWEST CORNER OF SECTION 10-20-13.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS SOUTH ON THE SECTION LINE FOR 1,140 FEET TO A POST HE SET FOR AN ANGLE TO THE SOUTHEASTERLY DUE TO THE NEOSHO RIVER
- 7) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK “C” ON THE RIGHT PAGE 156 DATED MAY 16, 1878, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 10-20-13 ON THIS ROAD SURVEY.
- 8) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 54 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE SOUTHWEST CORNER OF SECTION 3-20-13 AT 5,267 FEET SOUTH OF THE NORTHWEST CORNER OF SECTION 3-20-13 ON THE TOWNSHIP LINE.
- 1) 28’ NW TO A WITNESS PIN BY A CORNER POST ABOUT 8” EAST OF THE POST
  - 2) 43’ NE TO A WITNESS PIN 1’ SOUTHEAST OF A LARGE CORNER POST
  - 3) 24.83’ SW TO A BIG ELM TREE
- 9) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 20-13 SHOWS A **REA PIN** AT THE “SW CORNER SECTION 3-20-13”. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS PIN WAS PROBABLY “HEELED-IN” FOR UTILITY USE ONLY - WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 28’ NW TO A WITNESS [REA]
  - 2) 43’ NE TO A WITNESS [REA]
  - 3) 24.83’ SW TO AN ELM TREE
- 10) LLOYD J. DOBLER, L.S. 541, OF PROFESSIONAL ENGINEERING CONSULTANTS, FOR CONTRACT DACW56-70-C-0158, FOR THE “PARTIAL BOUNDARY SURVEYS “AREA A” JOHN REDMOND RESERVOIR” SURVEYED NOVEMBER 1970 AND FIELD NOTES RECORDED IN SURVEY BOOK NUMBER 5-1790, SURVEY F03001 IN THE SURVEY FILE FOR TOWNSHIP 19-13, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND AN**

**IRON PIN AT THE SOUTHWEST CORNER OF SECTION 3-20-13. HE DID NOT DESCRIBE THE IRON PIN OR TURN IN ANY TIES TO THE COUNTY ENGINEER'S OFFICE. VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THE JOHN REDMOND SURVEYS WERE POORLY RESEARCHED AND LITTLE, IF ANY, SEARCH WAS MADE FOR THE STONES OF RECORD – AND HE DID NOT FIND THE STONE AT THE SOUTHEAST CORNER OF SECTION 3-20-13, SO HIS DISTANCE BELOW TO THE “IRON PIN” THAT HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 3 MAY NOT BE CORRECT – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**

- ~~1) 2,627.25' NORTH TO THE “ORIGINAL STONE” HE FOUND AT THE WEST 1/4 CORNER OF SECTION 3-20-13~~
- ~~2) 5,267.30' NORTH TO THE IRON PIN HE FOUND AT THE NORTHWEST CORNER OF SECTION 3-20-13~~
- ~~3) 2,666.36' EAST TO AN IRON PIN HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 3-20-13~~
- ~~4) 5,328.91' EAST TO AN IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-20-13~~

**[SEE THE NOTE ABOUT THE STONE AT THE SOUTHEAST CORNER OF SECTION 3-20-13 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**

NORTHWEST CORNER 10-20-13