

WEST 1/4 CORNER SECTION 10, TOWNSHIP 20 SOUTH, RANGE 13 EAST

- 1) ON PAGE 672 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 9 & 10-20-13.
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 8, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 8 DATED FEBRUARY 2 & 3, 1870 TO ESTABLISH TO THE NORTHWEST CORNER OF SECTION 15 IN TOWNSHIP 20, RANGE 13, SAID THAT **HE FOUND THE STONE AT THE WEST 1/4 CORNER OF SECTION 10-20-13 ON THIS PERMANENT SURVEY.**
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 2,640' SOUTH TO THE STONE HE SET FOR THE NORTHWEST CORNER OF SECTION 15-20-13
 - 2) 5,280' SOUTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 15-20-13
- 3) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 51, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 50 DATED JUNE 8, 1870 TO ESTABLISH THE NORTHWEST CORNER OF SECTION 9, THE CENTER CORNER OF SECTION 9, AND THE CENTER CORNER OF THE NORTHEAST 1/4 OF SECTION 9, ALL IN TOWNSHIP 20 OF RANGE 13, SAID THAT **HE FOUND THE STONE AT THE EAST 1/4 CORNER OF SECTION 9-20-13 ON THIS PERMANENT SURVEY.**
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 79.72 CHAINS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 9-20-13
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 136, A ROAD SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 135 DATED JULY 26, 1871 FOR A ROAD PETITIONED BY L. R. WRIGHT, ET. AL. FOR A ROAD IN TOWNSHIP 20, RANGE 13, SAID THAT **HE FOUND THE STONE AT THE WEST 1/4 CORNER OF SECTION 10-20-13 TO END THIS ROAD SURVEY.**
- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 5 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 152 DATED JANUARY 23, 1872 TO ESTABLISH THE CENTER OF SECTION 10-20-12, DIVIDE THE SOUTHWEST 1/4 EQUALLY BY A LINE RUNNING NORTH & SOUTH, AND TO SUBDIVIDE THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 10, SAID THAT **HE FOUND THE STONE AT THE WEST 1/4 CORNER OF SECTION 10-20-13 ON THIS PERMANENT SURVEY.**
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,346.75' EAST TO THE TRUE LOCATION OF THE NORTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 10-20-13 – FALLS IN THE NEOSHO RIVER
 - 2) 1,574.75' EAST TO THE WITNESS STONE HE SET ON THE LEFT BANK OF THE NEOSHO RIVER
 - 3) 2,693.5' EAST TO THE STONE POST HE SET FOR THE CENTER CORNER OF SECTION 10-20-13
 - 4) 5,332' EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 10-20-13 ON THE LYON AND COFFEY COUNTY LINE

WEST QUARTER CORNER 10-20-13