

CENTER CORNER OF SECTION 15, TOWNSHIP 20 SOUTH, RANGE 13 EAST

- 1) E. B. KIRKENDALL, COUNTY SURVEYOR FROM 1863 TO 1865, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "A" ON PAGE 40 [PACKET 160 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY S. VANGUNDY AND OTHER FOR THE "NEOSHO RAPIDS TO HARTFORD ROAD" THAT WAS SURVEYED JULY 15 & 16, 1863, AND ESTABLISHED IN THE COMMISSIONERS JOURNAL ON PAGE 49, SAID THAT HE COMMENCED THIS ROAD SURVEY AT A POINT **7.50 CHAINS EAST** OF THE SOUTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 15-20-13.
- 2) D. T. McAULEY, WITH THE CONSENT OF JAMES MEANS, COUNTY SURVEYOR FROM 1865 TO 1867, IN SURVEY NUMBER 2 RECORDED IN SURVEY BOOK "A" ON PAGE 95 DATED NOVEMBER 1867 FOR LOTS IN PART OF SECTION 15-20-13, SAID THAT HE BEGAN THIS SURVEY AT THE CENTER CORNER OF SECTION 15-20-13. HE DOES NOT DESCRIBE THE MONUMENT THAT HE FOUND AT THIS CORNER.
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 110 RECORDED IN SURVEY BOOK "A" ON PAGE 201 DATED APRIL 28 THROUGH MAY 1, 1869 FOR THE SURVEY OF A COUNTY ROAD PETITIONED BY W. H. PRIEST AND OTHERS IN TOWNSHIP 20, RANGE 13, SAID THAT HE BEGAN THIS ROAD SURVEY AT **THE CENTER OF SECTION 15-20-13 AT A STONE SET IN THE GROUND.**
- 4) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 131 & 132 [PACKET 261 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY W. H. PRIEST AND OTHERS FOR THE HARTFORD TO EMPORIA ROAD THAT WAS SURVEYED APRIL 29 & 30 AND MAY 1, 1869, WAS RECORDED IN THE COMMISSIONERS JOURNAL ON PAGE 272, AND ESTABLISHED AS A PUBLIC HIGHWAY ON JULY 5, 1869 AND FILED AND RECORDED ON JULY 5, 1969 BY J. L. WILLIAMS, COUNTY CLERK, SAID THAT HE BEGAN THIS ROAD SURVEY AT THE CENTER CORNER OF SECTION 15-20-13 **AT A STONE SET IN THE GROUND.** HE NOTED THAT THE WIDTH FROM THE BEGINNING OF THIS ROAD SURVEY AT THE CENTER CORNER OF SECTION 15-20-13 TO THE SOUTHEAST CORNER OF SECTION 19-1-12 WAS TO BE 60 FEET WIDE, AND THE REMAINDER OF THE ROAD TO THE TERMINUS AT THE SOUTH BOUNDARY OF EMPORIA TOWNSITE WAS "TO CONFORM TO THE WIDTH OF A ROAD ALREADY ESTABLISHED, IT INTERSECTING A COUNTY ROAD" AT THE TERMINUS OF THIS ROAD SURVEY.
 - 1) THIS ROAD EXTENDS WEST ON THE 1/2 SECTION LINES TO THE WEST 1/4 CORNER OF SECTION 16-20-13 AT A TURN TO THE NORTHWESTERLY ACCORDING TO HIS DRAWING
- 5) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 153, TERM 2, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 76 DATED JANUARY 26, 1909 AT THE ORDER OF J. D. HOPKINSON, SAID THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 15-20-13 ON THIS **PERMANENT SURVEY.**

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 26 RODS EAST TO THE IRON PIN STAKE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE J. D. HOPKINSON TRACT
 - 2) 30 RODS EAST TO THE IRON PIN STAKE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF THE J. D. HOPKINSON TRACT
- 6) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F15007 IN THE SURVEY FILE FOR TOWNSHIP 20-13 FOR A SURVEY TO LOCATE THE CORNERS TO A PARCEL OF LAND LOCATED IN THE SOUTHWEST QUARTER OF

SECTION 15-20-13, SHOWS ON HIS SURVEY DRAWING A “**MONUMENT**” AT THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 15-20-13. THE SURVEY WAS SIGNED BY HAL GIBSON AND IT WAS NOT DATED. THERE IS NO DESCRIPTION OF THE MONUMENT AT THIS CORNER AND THERE ARE NO TIES ON THE SURVEY.

- 7) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN AN **INFORMAL SURVEY** RECORDED IN PERMANENT SURVEY BOOK NUMBER 2 ON PAGE 5 AND DATED JULY 9, 1954 AT THE REQUEST OF RAY BUXTON TO MARK HIS TRACT IN THE NORTHWEST 1/4 OF SECTION 15-20-13, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE CENTER CORNER OF SECTION 15-20-13 ON THIS **INFORMAL SURVEY**. THERE ARE NO TIES ON THE SURVEY. **HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
 - 1) 1,323’ WEST TO THE TEMPORARY POINT HE SET FOR THE SOUTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 15-20-13
 - 2) 2,646’ WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 15-20-13

- 8) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 41, FOR THE LEVEE RIGHT OF WAY LOCATION IN HARTFORD, KANSAS AS REQUESTED BY THE U. S. CORPS OF ENGINEERS IN TULSA, OKLAHOMA THAT BEGAN ON MARCH 16, 1962 AND WAS COMPLETED ON APRIL 4, 1962 SAID IN HIS FIELD NOTES THAT **HE FOUND THE STONE AND REBAR** AT THE CENTER CORNER OF SECTION 15-20-13 ON THIS **PERMANENT SURVEY**. THERE ARE NO TIES ON THE SURVEY. **HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:**
 - 1) 2,646.0’ WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 15-20-13
 - 2) 2,353.15’ EAST TO THE 1/2" DIAMETER REBAR HE SET FOR POINT #7 ON THE LEVEE RIGHT-OF-WAY LINE
 - 3) 2,668.6’ EAST TO THE GAS PIPE OVER A 1/2" DIAMETER REBAR HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE SE1/4 OF SECTION 15-20-13 ON THE LYON AND COFFEY COUNTY LINE

- 9) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN LARGE SURVEY SR #15001 IN THE SURVEY DRAWER FOR TOWNSHIPS 20-10 TO 20-13 DATED APRIL 4, 1962 FOR THE LEVEE RIGHT OF WAY LOCATION IN HARTFORD, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A STONE AND REBAR** AT THE CENTER CORNER OF SECTION 15-20-13. THERE ARE NO TIES ON THE SURVEY. **HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
 - 1) 2,646.0’ WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 15-20-13
 - 2) 2,353.15’ EAST TO THE 1/2" DIAMETER REBAR HE SET FOR POINT #7 ON THE LEVEE RIGHT-OF-WAY LINE
 - 3) 2,668.6’ EAST TO THE GAS PIPE OVER A 1/2" DIAMETER REBAR HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE SE1/4 OF SECTION 15-20-13 ON THE LYON AND COFFEY COUNTY LINE

- 10) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 20-13 SHOWS A **SANDSTONE & IRON PIN** AT THE “CENTER CORNER SECTION 15-20-13”.
 - 1) 35’ NW TO AN EVERGREEN TREE
 - 2) 52.4’ NE TO AN EVERGREEN TREE
 - 3) 60.4’ NE TO THE SOUTHWEST CORNER OF A HOUSE
 - 4) 3.3’ NORTH OF A BRICK WALK

CONTINUED ON PAGE 3

- 11) NORMAN T. COOK, L.S. 169, IN SURVEY F15028 IN THE SURVEY FILE FOR TOWNSHIP 20-13 FOR A PARTIAL BOUNDARY SURVEY FOR JOHN REDMOND RESERVOIR GRAND (NEOSHO) RIVER UNDER CONTRACT NUMBER DACW 56-69-C-0124 RECORDED IN FIELD BOOK 5-1769 DATED OCTOBER 1, 1969 SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE “ORIGINAL CORNER”** AT THE CENTER CORNER OF SECTION 15-20-13. THERE IS NO DESCRIPTION OF THE MONUMENT THAT HE FOUND AT THE “ORIGINAL CORNER” AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 710.00’ WEST TO THE “MONUMENT” HE SET FOR THE CORPS BOUNDARY – NOT DESCRIBED
 - 2) 788.49’ WEST TO THE “MONUMENT” HE SET FOR THE CORPS BOUNDARY – NOT DESCRIBED
 - 3) 2,645.97’ WEST TO THE “ORIGINAL CORNER” HE FOUND AT THE WEST 1/4 CORNER OF SECTION 15-20-13 – NOT DESCRIBED
 - 4) 670.00’ NORTH TO THE “MONUMENT” HE SET FOR THE CORPS BOUNDARY – NOT DESCRIBED
 - 5) ~~2,635.43’ NORTH TO THE IRON PIN HE SET FOR THE NORTH 1/4 CORNER OF SECTION 15-20-13.~~ **NOTE: SEE THE REFERENCE TIES FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 15-20-13 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 12) STEVEN S. BROSEMER, L.S. 752, IN SURVEY F15025 IN THE SURVEY FILE FOR TOWNSHIP 20-13 FOR TWO PREVIOUSLY DESCRIBED TRACTS LOCATED IN THE NORTHEAST QUARTER OF SECTION 15-20-13 DATED AUGUST 2, 1984, AND RECORDED IN VOLUME 409 ON PAGE 807 IN THE REGISTER OF DEEDS OFFICE ON AUGUST 6, 1984, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 15-20-13. HE NOTED THAT THERE WERE REFERENCE TIES ON FILE, BUT THEY HAVE APPARENTLY BEEN REMOVED FROM THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 494.9’ EAST TO THE 3/4" IRON PIN HE FOUND THAT WAS SET BY YINGLING IN A 1909 PERMANENT SURVEY
 - 2) 440.22’ NORTH TO THE 1/2" REBAR WITH HIS RED “LS 752” CAP HE SET FOR THE SOUTHWEST CORNER OF TRACT “A”
 - 3) 525.22’ NORTH TO THE 1/2" REBAR WITH HIS RED “LS 752” CAP HE SET FOR THE NORTHWEST CORNER OF TRACT “A”
- 13) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED JULY 18, 1997, **FOUND A SANDSTONE 5” NORTH-SOUTH BY 2” EAST-WEST, WITH THE TOP OF THE STONE AT 2” BELOW THE GROUND, WITH A 1/2” REBAR AT THE NORTHWEST CORNER OF THE STONE** AT THE CENTER CORNER OF SECTION 15-20-13. THIS STONE IS IN THE YARD AREA BETWEEN 204 AND 208 WEST MAPLE STREET IN HARTFORD, AND WAS FOUND WITH THE ASSISTANCE OF WM. H. PETERSON OF 208 WEST MAPLE STREET. I USED TIES FROM THE 1962 LEVEE SURVEY BY LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, AND TIES IN THE KRETSINGER REFERENCE TIE BOOKS FOR THIS TOWNSHIP TO FIND THIS STONE.
- 1) 60.3’ NE TO THE SW CORNER OF THE HOUSE AT 204 WEST MAPLE STREET
 - 2) 8.9’ EAST TO THE WEST FACE OF A TWIN 50’ SILVER MAPLE
 - 3) 28.3’ SOUTH TO THE TOP CENTERLINE AT THE EAST END OF A 10” CORRUGATED METAL PIPE ENTRANCE CULVERT
 - 4) 35.5’ SW TO THE TOP CENTERLINE AT THE WEST END OF A 10” CORRUGATED METAL PIPE ENTRANCE CULVERT
 - 5) 48.4’ SOUTH TO THE TRAVELED WAY OF MAPLE STREET EAST-WEST
 - 6) 190.4’ EAST TO THE TRAVELED WAY OF MECHANIC STREET TO THE SOUTH

- 14) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED NOVEMBER 10, 2003, FOR PROJECT NUMBER 00296-02, SAID THAT **HE FOUND THE 1/2" SQUARE REBAR ON THE WEST SIDE OF THE STONE** AT THE CENTER CORNER OF SECTION 15-20-13 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYORS OFFICE.
- 1) 48.3' SOUTH TO THE CENTERLINE TRAVELED WAY EAST-WEST
 - 2) 9.6' EAST TO A 40 D SPIKE & WASHER IN A 24" BIRCH TREE
 - 3) 54.4' SW TO A 40 D SPIKE & WASHER IN A POWER POLE
 - 4) 53.5' NNE TO THE FRONT FACE OF A CORNER CHAIN LINK FENCE POST
 - 5) 75.5' SSW TO A 40 D SPIKE & WASHER IN A POWER POLE
- 15) FRANKE SINKER, L.S. 1086, KDOT SURVEYOR, IN A SECTION CORNER REPORT DATED NOVEMBER 25, 2003, FOR KDOT PROJECT NUMBER 130-56 K-7445-01, SAID THAT **HE FOUND A 12" [V] X 11" [N-S] X 2.5" [E-W] YELLOW LIMESTONE AT 5" DEEP WITH A 1/2" SQUARE REBAR AT THE CENTERLINE OF THE WEST FACE OF THE STONE AT 5" DEEP** AT THE CENTER CORNER OF SECTION 15-20-13. HE SAID THAT THIS STONE WAS RECOVERED IN THREE DISTINCT PIECES. HE USED A LYON COUNTY SECTION CORNER REPORT FILED BY WARREN CHIP WOODS [LYON COUNTY SURVEYOR] DATED JULY 14, 1997, TO RECOVER THIS MONUMENT. HE SAID THAT ALTHOUGH THE SIZE AND TYPE OF MONUMENT DIFFER FROM MR. WOODS DESCRIPTION, OUR REFERENCE DISTANCE MATCHES HIS DISTANCES EXTREMELY WELL. KDOT CORNER NUMBER 15003
- 1) 60.35' NNE TO THE SOUTHWEST CORNER [AT THE GROUND] OF THE HOUSE AT "204 WEST MAPLE STREET"
 - 2) 103.2' NNW TO THE SOUTHEAST CORNER [AT THE GROUND] OF THE HOUSE AT "208 WEST MAPLE STREET"
 - 3) 16.0' WEST TO THE TRAVELED WAY OF THE N-S GRAVEL DRIVEWAY [208 WEST MAPLE]
 - 4) 48.4' SOUTH TO THE TRAVELED WAY OF EAST-WEST PAVED MAPLE STREET
 - 5) 28.3' SOUTH TO THE CENTERLINE AT THE TOP AT THE EAST END OF A 10" X 24" CORRUGATED METAL PIPE ENTRANCE PIPE
 - 6) 35.5' SW TO THE CENTERLINE AT THE TOP AT THE WEST END OF A 10" X 24" CORRUGATED METAL PIPE ENTRANCE PIPE
 - 7) 8.5' EAST TO THE WEST FACE OF A TWIN 50" SILVER MAPLE AT THE GROUND
 - 8) 54.5' WSW TO A SPIKE & BOTTLE CAP [EXISTENT] IN THE NORTHEAST FACE OF A TELEPHONE CABLE POLE
 - 9) 75.3' SSW TO A SPIKE & FLAT WASHER [EXISTENT] IN THE NORTHWEST FACE OF A POWER POLE
- A DRAWING SIGNED BY LARRY DEE MOORE, R.L.S. 1174 DATED JANUARY 30, 2004 SHOWS THE FOLLOWING INFORMATION:
- 1) STATE PLANE COORDINATES: N = 1921094.354 E = 2041342.287
 - 2) 2,646.29' WEST TO THE REBAR WITH A RED PLASTIC CAP STAMPED LYON COUNTY IN AN 8" DIAMETER CAST IRON THIMBLE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 15-20-13
 - 3) 2,667.89' EAST TO THE 1.75" O. D. STEEL PIPE HE FOUND AT 36" DEEP AT THE EAST 1/4 CORNER OF SECTION 15-20-13 ON THE LYON AND COFFEY COUNTY LINE
 - 4) 7,981.33' EAST TO THE 9" X 4.5" X 12" WHITE LIMESTONE HE FOUND AT 18' DEEP AT THE EAST 1/4 CORNER OF SECTION 14-20-13 IN COFFEY COUNTY
 - 5) 2,635.82' NORTH TO THE 10" X 2.5" X 23" LIMESTONE HE FOUND AT THE SURFACE AT THE NORTH 1/4 CORNER OF SECTION 15-20-13
 - 6) 5,280.09' NORTH TO THE 9" X 6.5" X 16" YELLOW LIMESTONE HE FOUND AT 6" DEEP AT THE CENTER CORNER OF SECTION 10-20-13
- 16) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED JUNE 4, 2009 FOR PROJECT NUMBER 09126-02, SAID THAT

HE FOUND THE STONE WITH THE #4 SQUARE REBAR ON THE WEST SIDE OF THE STONE AT THE CENTER CORNER OF SECTION 15-20-13 FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE. THIS SURVEY WAS FOR BLOCK 37 AND THE VACATED ALLEY IN BLOCK 37 AND THE VACATED PORTION OF WEST STREET ADJACENT TO BLOCK 37 AND VACATED GRAND AVENUE NORTH OF BLOCK 37 IN THE TOWN OF HARTFORD, AND IS FILED IN THE *TOWN OF HARTFORD* FILE IN THE DRAWER FOR TOWNSHIP 20-13.

- 1) 54.35' WSW TO A CONCRETE NAIL & BOTTLECAP IN THE NORTHEAST FACE OF
- 2) 75.15' SSW TO A CONCRETE NAIL & BOTTLECAP IN THE NORTHEAST FACE OF A POWER POLE
- 3) 28.5' SOUTH TO THE TOP CENTER OF THE EAST END OF A 12" CMP
- 4) 35.4' SW TO THE TOP CENTER OF THE EAST END OF A 12" CMP
- 5) 49' SOUTH TO THE CENTERLINE TRAVELED WAY OF MAPLE STREET EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,646.35' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 15-20-13
- 2) 2,636.37' SOUTH TO THE RAILROAD SPIKE OVER THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 15-20-13

- 17) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED NOVEMBER 11, 2010 FOR PROJECT NUMBER 10312-02, SURVEY F15029 IN THE SURVEY FILE FOR TOWNSHIP 20-13 FOR THE SURVEY OF A TRACT IN THE SOUTHWEST QUARTER OF SECTION 15-20-13 FOR ROBERTS, SAID THAT **HE FOUND THE STONE WITH A #4 SQUARE REBAR ON THE WEST SIDE** AT THE CENTER CORNER OF SECTION 15-20-13 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY SURVEYOR'S OFFICE.

- 1) 54.35' WSW TO A CONCRETE NAIL & BOTTLECAP IN THE NORTHEAST FACE OF A POWER POLE
- 2) 75.15' SSW TO A CONCRETE NAIL & BOTTLECAP IN THE NORTHEAST FACE OF A POWER POLE
- 3) 28.5' SOUTH TO THE TOP CENTER OF THE EAST END OF A 12" CMP
- 4) 35.4' SW TO THE TOP CENTER OF THE EAST END OF A 12" CMP
- 5) 49' SOUTH TO THE CENTERLINE TRAVELED WAY OF MAPLE STREET EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,636.05' SOUTH TO THE 1-1/4" IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 15-20-13

- 18) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED JULY 7, 2011 FOR PROJECT NUMBER 11111-02, IN SURVEY F15031 IN THE SURVEY FILE FOR TOWNSHIP 20, RANGE 13, A SURVEY FOR THREE TRACTS IN THE SOUTHWEST 1/4 OF SECTION 15-20-13 FOR KENNY HAMMAN, SAID THAT **HE FOUND THE STONE WITH THE #4 SQUARE REBAR ON THE WEST SIDE** AT THE CENTER CORNER OF SECTION 15-20-13 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE. HE NOTED THAT THE STONE WAS FOUND BY LESLIE M. GOULD IN 1954.

- 1) 54.35' WSW TO A CONCRETE NAIL & BOTTLECAP IN THE NORTHEAST FACE OF A POWER POLE
- 2) 75.15' SSW TO A CONCRETE NAIL & BOTTLECAP IN THE NORTHEAST FACE OF A POWER POLE
- 3) 28.5' SOUTH TO THE TOP CENTER OF THE EAST END OF A 12" CMP
- 4) 35.4' SW TO THE TOP CENTER OF THE EAST END OF A 12" CMP
- 5) 49' SOUTH TO THE CENTERLINE TRAVELED WAY OF MAPLE STREET EAST AND WEST

HIS INFORMATION IS CONTINUED ON PAGE 6

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,646.43' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 15-20-13
- 2) 2,636.24' SOUTH TO THE 1-1/4" IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 15-20-13

CENTER CORNER 15-20-13