

**NORTH 1/16 CORNER NORTHWEST 1/4 SECTION 15, TOWNSHIP 20 SOUTH, RANGE 13 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 8, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 8 DATED FEBRUARY 2 & 3, 1870 TO ESTABLISH TO THE NORTHWEST CORNER OF SECTION 15 IN TOWNSHIP 20, RANGE 13, SAID THAT **HE SET A TEMPORARY STAKE** AT 1,320' WEST OF THE NORTH 1/4 CORNER OF SECTION 15-20-13. HE DID NOT SAY IF HE CAME BACK AND CORRECTED THE LOCATION TO BE ON TRUE LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 15-20-13 AND THE STONE THAT HE SET FOR THE NORTHWEST CORNER OF SECTION 15-20-13. HIS SURVEY DRAWING INDICATES THAT HE DID ESTABLISH THIS 1/2/4 CORNER.
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 176 & 177 [PACKET 24 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY S. E. G. HOLT AND OTHERS FOR A ROAD IN TOWNSHIP 20-13 THAT HE SURVEYED JULY 27, 1871, WAS ORDERED AND ESTABLISHED BY THE BOARD OF COUNTY COMMISSIONERS AS A 50 FOOT WIDE ROAD ON SEPTEMBER 4, 1871, AND WAS FILED FOR RECORD ON SEPTEMBER 4, 1871 BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT **HE FOUND** THE NORTH 1/2/4 CORNER OF THE NORTHWEST 1/4 OF SECTION 15-20-13 TO END THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS NORTH ON THE 1/2/4 SECTION LINE FOR 1,620 FEET TO A POST HE SET FOR AN ANGLE TO THE NORTHEASTERLY DUE TO THE NEOSHO RIVER
  
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 135, A ROAD SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 134 DATED JULY 25, 1871 FOR A ROAD IN SECTION 10-20-13, SAID THAT **HE FOUND THE STONE** ON THE SOUTH SIDE OF THE SOUTHWEST 1/4 OF SECTION 10-20-13 TO END THIS ROAD SURVEY.
  
- 4) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 36 DATED NOVEMBER 28, 1882, FOR A ROAD SURVEY IN TOWNSHIP 20, RANGE 13 FOR W. P. GOULD, PRINCIPAL PETITIONER, SAID THAT HE ENDED THIS ROAD SURVEY AT A POINT 51 RODS AND 8 LINKS SOUTH OF THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 15-20-13. HE SHOULD HAVE SET A STONE TO MARK THE END POINT ON THIS ROAD SURVEY.
  
- 5) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 200 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 386 TO 388 PETITIONED BY H. P. GOULD AND OTHERS FOR THE VACATION AND RELOCATION OF A COUNTY ROAD IN SECTION 15-20-13 [PACKET 479 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 28, 1882, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON JANUARY 3, 1883 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOAR OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 22, 1883 BY WILLIAM F. EWING, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 SECTION 15-20-13 AS HE ENDED THIS ROAD SURVEY AT A POINT 51 RODS AND 8 LINKS SOUTH OF THIS CORNER ON THE EAST LINE OF ATTICA TOWNSITE.

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) THIS ROAD ENDED AT THE POINT 51 RODS AND 8 LINKS SOUTH OF THE NORTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 15-20-13 AND EXTENDED EAST PARALLEL WITH THE NORTH LINE OF SECTION 15-21-13 FOR 110 RODS TO A POINT 51 RODS & 8 LINKS SOUTH AND 30 RODS EAST OF THE 1/4 CORNER ON THE NORTH LINE OF SECTION 15-20-13
  
- 6) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 140 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 146 TO 148 PETITIONED BY S. E. G. HOLT AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 20-13 [PACKET 428 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 27, 1881, AND WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 5, 1881 AS NOTED BY H. F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, SAID THAT SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 15-20-13 TO COMMENCE THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS SOUTH FOR 2,640 FEET TO THE SOUTHEAST CORNER OF THE W1/2 OF THE NORTHWEST 1/4 OF SECTION 15-20-13 TO THE HARTFORD AND EMPORIA ROAD AT THE TERMINUS OF THIS ROAD SURVEY
  
- 7) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON RIGHT SIDE PAGE 201 DATED DECEMBER 27, 1881, FOR A ROAD SURVEY IN TOWNSHIP 20-13 APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 15-20-13 TO COMMENCE THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THE ROAD EXTENDS 1/2 MILE SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 15-20-13 AT THE TERMINUS OF THIS ROAD SURVEY
  
- 8) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN AN INFORMAL SURVEY RECORDED IN PERMANENT SURVEY BOOK NUMBER 2 ON PAGE 5 AND DATED JULY 9, 1954 AT THE REQUEST OF RAY BUXTON TO MARK HIS TRACT IN THE NORTHWEST 1/4 OF SECTION 15-20-13, SHOWS ON HIS SURVEY DRAWING AN **IRON PIN** AT THE NORTHEAST CORNER OF THE WEST 1/2 OF THE NORTHWEST 1/4 OF SECTION 15-20-13 ON THIS INFORMAL SURVEY.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,349' WEST TO THE IRON PIN AT THE NORTHWEST CORNER OF SEC. 15-20-13
  - 2) 2,630' SOUTH TO THE TEMPORARY POINT HE SET FOR THE SOUTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 15-20-13

NORTH SIXTEENTH CORNER NORTHWEST QUARTER 15-20-13