

NORTH 1/4 CORNER OF SECTION 29, TOWNSHIP 20 SOUTH, RANGE 13 EAST

- 1) ON PAGE 679 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 10" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 29-20-13.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 39.88-1/2* CHAINS WEST TO THE 18" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-20-13
 - 2) 39.98-1/2 CHAINS EAST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-20-13
 - 3) * THIS IS THE REMAINING DISTANCE AFTER THEY CHAINED WEST ON A TRUE LINE FROM THE NORTHEAST CORNER OF SECTION 29-20-13 AND SET THE STONE AT THE 1/4 CORNER AT 39.98-1/2 CHAINS – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 18, 2008 FOR PROJECT NUMBER 08300-02, SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 20-13 FOR THE SURVEY OF A 7.43 ACRE TRACT IN THE NORTH HALF OF THE SOUTHEAST QUARTER AND A PREVIOUSLY DESCRIBED TRACT IN THE SOUTH HALF OF THE SOUTHEAST QUARTER OF SECTION 29-20-13 FOR DENNY DARBYSHIRE, SAID THAT **HE FOUND A 4" X 8" X 10" LIMESTONE WITH AN EYE BOLT BENT OVER THE TOP OF THE STONE AND ON THE EAST SIDE** AT THE NORTH 1/4 CORNER OF SECTION 29-20-13 FROM EXISTING REFERENCE TIES ON A SURVEY BY HIM IN 1987. [**NOTE:** HIS 1987 TIES ARE MISSING FROM THE SURVEY TIE FILES – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
- 1) 20.0' NE TO A CONCRETE NAIL & BOTTLE CAP IN THE TOP OF A BRACE POST
 - 2) 20.45' NNW TO A CONCRETE NAIL & BOTTLE CAP IN THE TOP OF A CORNER FENCE POST
 - 3) 28.9' SSW TO A CONCRETE NAIL & BOTTLE CAP IN THE TOP OF A CORNER FENCE POST
 - 4) 10' EAST TO A FENCE TO THE SOUTH
 - 5) 3.5' WEST TO A FENCE TO THE NORTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 2,614.17' WEST TO THE 1" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 29-20-13
 - 2) 2,662.55' SOUTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 29-20-13
 - 3) 3,988.77' SOUTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE S1/2 OF THE SE1/4 OF SECTION 29-20-13
 - 4) 5,314.99' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 29-20-13

NORTH QUARTER CORNER 29-20-13