

WEST 1/4 CORNER SECTION 29, TOWNSHIP 20 SOUTH, RANGE 13 EAST

- 1) ON PAGE 679 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 10" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 30-20-13.

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN LAND SURVEY REFERENCE REPORT DATED NOVEMBER 18, 2008 FOR PROJECT NUMBER 08300-02, SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 20-13 FOR THE SURVEY OF A 7.43 ACRE TRACT IN THE NORTH HALF OF THE SOUTHEAST QUARTER AND A PREVIOUSLY DESCRIBED TRACT IN THE SOUTH HALF OF THE SOUTHEAST QUARTER OF SECTION 29-20-13 FOR DENNY DARBYSHIRE, SAID THAT HE DEEMED THAT THE WEST 1/4 CORNER OF SECTION 29-20-13 WAS **LOST. HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE WEST 1/4 CORNER OF SECTION 29-20-13 ON TRUE LINE AND HALFWAY BETWEEN THE NORTHWEST AND SOUTHWEST SECTION CORNERS OF SECTION 29-20-13.
 - 1) 30.9' EAST TO A CONCRETE NAIL & BOTTLECAP IN THE TOP OF A CORNER FENCE POST
 - 2) 29.9' ESE TO A CONCRETE NAIL & BOTTLECAP IN THE TOP OF A BRACE POST
 - 3) 1' NORTH TO THE CENTERLINE OF A FENCE TO THE EAST
 - 4) 2.4' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "W" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,657.87' NORTH TO THE 1" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 29-20-13
 - 2) 2,657.87' SOUTH TO THE MAG NAIL HE SET IN ASPHALT FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 29-20-13
 - 3) 2,638.65' EAST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 29-20-13
 - 4) 5,235.57' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 29-20-13

WEST QUARTER CORNER 29-20-13